Printing date 09/25/2015

Reviewed on 09/25/2015

1 Identification

- · Product identifer
- · Trade name: <u>MC-FERROX A 100</u>
- · Article number: W231.X W231.XX W231.XXXX
- Details of the supplier of the safety data sheet • Manufacturer/Supplier:
- Wasser Corporation 4118 B PL NW, Suite B Auburn, WA 98001, US Phone 253-850-2967
- Information department: Product safety department
 Emergency telephone number: EMERGENCY PHONE NUMBERS: USA and Canada: 1-800 424-9300 International: 1-703 527-3887

2 Hazard(s) identification

· Classification of the substance or mixture



Flam. Liq. 2 H225 Highly flammable liquid and vapor.



Resp. Sens. 1H334May cause allergy or asthma symptoms or breathing difficulties if inhaled.Muta. 1BH340May cause genetic defects.Carc. 1AH350May cause cancer.



Acute Tox. 4	H332	Harmful if inhaled.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2A	H319	Causes serious eye irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H335	May cause respiratory irritation.

· Label elements

· GHS label elements

The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

• *Hazard-determining components of labeling: titanium dioxide Hexane, 1,6-diisocyanato-, homopolymer Stoddard solvent*

(Contd. on page 2)

- US

US

Printing date 09/25/2015

Reviewed on 09/25/2015

Trade name: MC-FERROX A 100

	(Contd. of page 1)
Ferric oxide	
· Hazard statem	ents
	ammable liquid and vapor.
H332 Harmful	
H315 Causes st	kin irritation.
H319 Causes se	erious eye irritation.
H334 May caus	e allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May caus	se an allergic skin reaction.
H340 May caus	se genetic defects.
H350 May caus	se cancer.
H335 May caus	se respiratory irritation.
· Precautionary	statements
Keep out of rea	ch from children.
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P284	Wear respiratory protection.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P280	Wear protective gloves / eye protection / face protection.
P280	Wear protective gloves.
P280	Wear eye protection / face protection.
P240	Ground/bond container and receiving equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
	353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
$P305 \pm P351 \pm P$	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if
1505 11551 11	present and easy to do. Continue rinsing.
P321	Specific treatment (see on this label).
P342+P311	If experiencing respiratory symptoms: Call a poison center/doctor.
P304+P340	<i>IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for</i>
150111510	breathing.
P312	Call a poison center/doctor if you feel unwell.
P363	Wash contaminated clothing before reuse.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use for extinction: CO2, powder or water spray.
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international
1001	regulations.
· Classification s	0
· NFPA ratings	
	Iealth = 3
	Fire = 3
	Reactivity = 0
▼ ∨	
	(Contd. on page 3)

(Contd. of page 2)

Safety Data Sheet acc. to OSHA HCS

Printing date 09/25/2015

Reviewed on 09/25/2015

Trade name: MC-FERROX A 100

· HMIS-ratings (scale 0 - 4)

HEALTH	*3	Health = *3
		Fire = 3
REACTIVITY	0	<i>Reactivity</i> =

· Other hazards

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

3 Composition/information on ingredients

0

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:		
1309-37-1	Ferric oxide	10-30%%
13463-67-7	titanium dioxide in pastel or grey colors	10-30%%
540-88-5	tert-butyl acetate	10-30%%
14807-96-6	Talc (Mg3H2(SiO3)4)	10-30%%
8052-41-3	Stoddard solvent	1-5%%
7429-90-5	aluminium powder (stabilised) only in aluminum color	1-5%%
28182-81-2	Hexane, 1,6-diisocyanato-, homopolymer	1-5%%
53880-05-0	Homopolymer of IPDI	1-5%%
110-43-0	methyl amyl ketone	1-5%%
1333-86-4	Carbon black in grey or dark colors	0.1-1%%
64742-95-6	Solvent naphtha (petroleum), light arom.	0.1-1%%
4098-71-9	isophorone di-isocyanate	0.1-1%%
95-63-6	1,2,4-trimethylbenzene	0.1-1%%
14808-60-7	Quartz (SiO2)	0.1-1%%
64742-82-1	Naphtha (petroleum), hydrodesulfurized heavy	0.1-1%%
64741-65-7	Naphtha (petroleum), heavy alkylate	0.1-1%%

4 First-aid measures

· Description of first aid measures

• General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

• After skin contact: Immediately wash with water and soap and rinse thoroughly.

• After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: If symptoms persist consult doctor.

· Information for doctor:

• Most important symptoms and effects, both acute and delayed No further relevant information available.

• *Indication of any immediate medical attention and special treatment needed No further relevant information available.*

(Contd. on page 4)

[•] After inhalation:

Printing date 09/25/2015

Reviewed on 09/25/2015

(Contd. of page 3)

5 Fire-fighting measures

Trade name: MC-FERROX A 100

- · Extinguishing media
- Suitable extinguishing agents: CO2, sand, extinguishing powder. Do not use water.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- Protective equipment: Mouth respiratory protective device.

6 Accidental release measures

- Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.
- Environmental precautions:
- Do not allow product to reach sewage system or any water course. Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up: Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
- **Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions:
- Keep receptacle tightly sealed.
- Store in cool, dry conditions in well sealed receptacles.
- · Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

(Contd. on page 5)

Printing date 09/25/2015

Reviewed on 09/25/2015

Trade name: MC-FERROX A 100

Compon 540-88-5 PEL Loi REL Loi TLV Loi	parameters nents with limit values that require monitoring at the workplace: 5 tert-butyl acetate mg-term value: 950 mg/m ³ , 200 ppm ong-term value: 950 mg/m ³ , 200 ppm ong-term value: 950 mg/m ³ , 200 ppm
PEL Loi REL Loi TLV Loi	ng-term value: 950 mg/m³, 200 ppm ng-term value: 950 mg/m³, 200 ppm
REL Loi TLV Loi	ng-term value: 950 mg/m³, 200 ppm
TLV Loi	
	ng tarm value: 050 mg/m ³ 200 ppm
	mg-lenm value. 950 mg/m², 200 ppm
8052-41-	-3 Stoddard solvent
PEL Loi	ng-term value: 2900 mg/m³, 500 ppm
Cet	ng-term value: 350 mg/m³ ;iling limit value: 1800* mg/m³ 5-min
TLV Loi	ng-term value: 525 mg/m³, 100 ppm
110-43-0	0 methyl amyl ketone
PEL Loi	ng-term value: 465 mg/m³, 100 ppm
REL Loi	ng-term value: 465 mg/m³, 100 ppm
TLV Loi	ng-term value: 233 mg/m³, 50 ppm
4098-71-	-9 isophorone di-isocyanate
	ort-term value: 0.18 mg/m³, 0.02 ppm mg-term value: 0.045 mg/m³, 0.005 ppm in
TLV Loi	ng-term value: 0.045 mg/m³, 0.005 ppm
Addition	nal information: The lists that were valid during the creation were used as basis.

- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin.

· Breathing equipment:

During mixing, handling and application: Splash goggles. Full protective clothing. Gloves (impervious). Wear suitable respiratory equipment. When air concentrations are not known (or above the TLV), an air-supplied respirator is required. Refer to OSHA Respiratory Protection Standard (29 CFR 1910.134).In presence of air movement, air-purifying (cartridge type) respirators are not the best protection but can be used, if you replaced them frequently. Change cartridges after 8h max or less due to their low warning properties. When in a confined space wear MSHA/NIOSH approved self-contained breathing apparatus or equivalent and full protective gear.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

(Contd. on page 6)

US

(Contd. of page 5)

Safety Data Sheet acc. to OSHA HCS

Printing date 09/25/2015

Reviewed on 09/25/2015

Trade name: MC-FERROX A 100

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

9 Physical and chemical properties · Information on basic physical and chemical properties · General Information · Appearance: Form: Fluid Color: Various colors · Odor: Aromatic · Odour threshold: Not determined. Not determined. · pH-value: · Change in condition Melting point/Melting range: Undetermined. Boiling point/Boiling range: 97 °C (207 °F) 15 °C (59 °F) · Flash point: · Flammability (solid, gaseous): Not applicable. · Ignition temperature: Decomposition temperature: Not determined. · Auto igniting: Product is not selfigniting. · Danger of explosion: Product is not explosive. However, formation of explosive air/vapor mixtures are possible. · Explosion limits: Lower: Not determined. Upper: Not determined. · Vapor pressure at 20 °C (68 °F): 41 hPa (31 mm Hg) • Density at 20 •C (68 •F): 1.53-1.77 g/cm³ (12.768-14.771 lbs/gal) · Relative density Not determined. · Vapour density Not determined. · Evaporation rate Not determined. · Solubility in / Miscibility with Not miscible or difficult to mix. Water: · Partition coefficient (n-octanol/water): Not determined. · Viscosity: Dynamic: Not determined. Kinematic: Not determined. · Solvent content: Solids content: 77.0-83.0 % No further relevant information available. • Other information

(Contd. on page 7)

Printing date 09/25/2015

Reviewed on 09/25/2015

(Contd. of page 6)

10 Stability and reactivity

Trade name: MC-FERROX A 100

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- *Conditions to avoid* No further relevant information available.
- *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity:

· LD/LC50 values that are	relevant fo	or classification:
---------------------------	-------------	--------------------

1309-37-1 Ferric oxide

Oral LD50 >5000 mg/kg (rat)

64742-95-6 Solvent naphtha (petroleum), light arom.

OralLD50>6800 mg/kg (rat)DermalLD50>3400 mg/kg (rab)

Inhalative LC50/4 h > 10.2 mg/l (rat)

64741-65-7 Naphtha (petroleum), heavy alkylate

 $\begin{array}{c|c} Oral & LD50 & > 6000 \ mg/kg \ (rat) \\ \hline \end{array}$

· Primary irritant effect:

• on the skin: Irritant to skin and mucous membranes.

- on the eye: Irritating effect.
- · Sensitization:

Sensitization possible through inhalation.

Sensitization possible through skin contact.

 \cdot Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

```
Irritant
```

Carcinogenic.

The product can cause inheritable damage.

· Carcinogenic categories

· IARC (Inter	rnational Agency for Research on Cancer)	
1309-37-1	Ferric oxide	3
13463-67-7	titanium dioxide	2B
14807-96-6	Talc (Mg3H2(SiO3)4)	2B
7631-86-9	silicon dioxide, chemically prepared	3
1333-86-4	Carbon black	28
14808-60-7	Quartz (SiO2)	1
1330-20-7	xylene	3
111-76-2	2-butoxyethanol	3
· NTP (Natio	nal Toxicology Program)	
14808-60-7	Quartz (SiO2)	K
		(Contd. on page 8

Printing date 09/25/2015

Reviewed on 09/25/2015

Trade name: MC-FERROX A 100

(Contd. of page 7)

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

12 Ecological information

- · Toxicity
- Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- \cdot **Mobility in soil** No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 3 (Self-assessment): extremely hazardous for water Do not allow product to reach ground water, water course or sewage system, even in small quantities. Danger to drinking water if even extremely small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation: Disposal must be made according to official regulations.

14 Transport information

UN-Number DOT, ADR, IMDG, IATA	UN1263	
UN proper shipping name		
DOT	Paint	
ADR	1263 Paint	
IMDG, IATA	PAINT	
Transport hazard class(es)		
DOT		
Class	3 Flammable liquids	
Label	3 3	
ADR, IMDG, IATA	,	
Class	3 Flammable liquids	

Printing date 09/25/2015

Reviewed on 09/25/2015

Trade name: MC-FERROX A 100

	(Contd. of pag
Label	3
Packing group DOT, ADR, IMDG, IATA	II
Environmental hazards: Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Danger code (Kemler):	33
EMS Number:	<i>F-E</i> , <u><i>S-E</i></u>
Transport in bulk according to Annex	II of
MARPOL73/78 and the IBC Code	Not applicable.
Transport/Additional information:	
DOT	
Quantity limitations	On passenger aircraft/rail: 5 L
	On cargo aircraft only: 60 L
ADR	
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
IMDG	
Limited quantities (LQ)	1L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
UN "Model Regulation":	UN1263, Paint, 3, II

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 35.	5 (extremely hazardous substances):		
4098-71-9	isophorone di-isocyanate		
· Section 31.	3 (Specific toxic chemical listings):		
4098-71-9	isophorone di-isocyanate		
95-63-6	1,2,4-trimethylbenzene		
1330-20-7	xylene		
822-06-0	hexamethylene-di-isocyanate		
872-50-4	N-methyl-2-pyrrolidone		
111-76-2	2-butoxyethanol		
· TSCA (Tox	xic Substances Control Act):		
Ferric oxid	le		
titanium di	oxide		
tert-butyl a	tert-butyl acetate		
Talc (Mg3)	Talc (Mg3H2(SiO3)4)		
Stoddard s	Stoddard solvent		
Hexane, 1,	Hexane, 1,6-diisocyanato-, homopolymer		
Homopoly	ner of IPDI		
methyl amy	il ketone		
	(Contd. on page 10)		

Printing date 09/25/2015

Reviewed on 09/25/2015

Trade name: MC-FERROX A 100

	(Contd. of page 9
silicon dioxide, chemically prepared	• •
· Proposition 65	
· Chemicals known to cause cancer:	
13463-67-7 titanium dioxide	
1333-86-4 Carbon black	
14808-60-7 Quartz (SiO2)	
· Chemicals known to cause reproductive toxicity for females:	
None of the ingredients is listed.	
· Chemicals known to cause reproductive toxicity for males:	
None of the ingredients is listed.	
• Chemicals known to cause developmental toxicity:	
872-50-4 N-methyl-2-pyrrolidone	
· Carcinogenic categories	
· EPA (Environmental Protection Agency)	
1330-20-7 xylene	I
111-76-2 2-butoxyethanol	NL
· TLV (Threshold Limit Value established by ACGIH)	
Ferric oxide	A4
titanium dioxide	A4
Talc (Mg3H2(SiO3)4)	A4
Carbon black	A4
Quartz (SiO2)	A2
zirconium dioxide	A4
xylene	A4
·NIOSH-Ca (National Institute for Occupational Safety and Health)	
13463-67-7 titanium dioxide	
1333-86-4 Carbon black	
14808-60-7 Quartz (SiO2)	
· GHS label elements	

The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

Hazard-determining components of labeling: titanium dioxide
Hexane, 1,6-diisocyanato-, homopolymer
Stoddard solvent
Ferric oxide
Hazard statements
H225 Highly flammable liquid and vapor.
H332 Harmful if inhaled.
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.

(Contd. on page 11)

US

Printing date 09/25/2015

Reviewed on 09/25/2015

Trade name: MC-FERROX A 100

	(Contd. of page 10)
	e genetic defects.
H350 May caus	
	e respiratory irritation.
· Precautionary s	
P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P284	Wear respiratory protection.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P280	Wear protective gloves / eye protection / face protection.
P280	Wear protective gloves.
P280	Wear eye protection / face protection.
P240	Ground/bond container and receiving equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P303+P361+P3	353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P305 + P351 + P351	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if
	present and easy to do. Continue rinsing.
P321	Specific treatment (see on this label).
P342 + P311	If experiencing respiratory symptoms: Call a poison center/doctor.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a poison center/doctor if you feel unwell.
P363	Wash contaminated clothing before reuse.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	In case of fire: Use for extinction: CO2, powder or water spray.
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. *Exceptions can be made by the authorities in certain cases.*

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department

· Contact: HS REG.DEPART.REG.SS

· Date of preparation / last revision 09/25/2015 / -

• Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation

IATA: International Air Transport Association

(Contd. on page 12)

US

Printing date 09/25/2015

Reviewed on 09/25/2015

(Contd. of page 11)

US

Trade name: MC-FERROX A 100

ACGIH: American Conference of Governmental Industrial Hygienists
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
NFPA: National Fire Protection Association (USA)
HMIS: Hazardous Materials Identification System (USA)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
Flam. Liq. 2: Flammable liquids, Hazard Category 2
Acute Tox. 4: Acute toxicity, Hazard Category 4
Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A
Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1
Skin Sens. 1: Sensitisation - Skin, Hazard Category 1
Muta. 1B: Germ cell mutagenicity, Hazard Category 1B
Carc. 1A: Carcinogenicity, Hazard Category 1A
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3