Printing date 11/29/2016

Reviewed on 09/02/2015

1 Identification

- · Product identifer
- · Trade name: <u>MC-CLEAR 100</u>
- · Article number: W271.0 W271.0SG
- \cdot Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Wasser Corporation 4118 B PL NW, Suite B Auburn, WA 98001, US Phone 253-850-2967

· Information department: Product safety department

• Emergency telephone number: EMERGENCY PHONE NUMBERS: USA and Canada: 1-800 424-9300 International: 1-703 527-3887

2 Hazard(s) identification

Classification of the substance or mixture
Flam. Liq. 2 H225 Highly flammable liquid and vapor.
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens. 1 H317 May cause an allergic skin reaction.
Muta. 1B H340 May cause genetic defects.
Carc. 1B H350 May cause cancer.
STOT SE 3 H335 May cause respiratory irritation.

· Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms*



· Signal word Danger

Hazard-determining components of labeling: Hexane, 1,6-diisocyanato-, homopolymer Solvent naphtha (petroleum), light arom. isophorone di-isocyanate hexamethylene-di-isocyanate
Hazard statements H225 Highly flammable liquid and vapor. H315 Causes skin irritation. H319 Causes serious eye irritation. H319 Causes serious eye irritation. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317 May cause an allergic skin reaction. H340 May cause genetic defects. H350 May cause cancer. H335 May cause respiratory irritation.

(Contd. on page 2)

⁻ US

Printing date 11/29/2016

Reviewed on 09/02/2015

Trade name: MC-CLEAR 100

Duccasticsam	(Contd. of page 1)
Precautionary s	ch from children.
P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.
P210 P241	
	Use explosion-proof electrical/ventilating/lighting/equipment.
P284	[In case of inadequate ventilation] wear respiratory protection.
P261	Avoid breathing dust/fume/gas/mist/vapors/spray
P280	Wear protective gloves / eye protection / face protection.
P240	Ground/bond container and receiving equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P303+P361+P3	353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P305+P351+P3	338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P321	Specific treatment (see on this label).
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P312	Call a POISON CENTER/doctor if you feel unwell.
P363	Wash contaminated clothing before reuse.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P333+P313	If exposed of concerned. Get medical davice/attention. If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P370+P378	
	In case of fire: Use for extinction: CO2, powder or water spray.
P362+P364	Take off contaminated clothing and wash it before reuse.
P405	Store locked up.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
Classification sy NFPA ratings (
F F	Mealth = 3 Vire = 3
	eactivity = 0

· HMIS-ratings (scale 0 - 4)

HEALTH	*3	Health = *3
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

• Other hazards

• Results of PBT and vPvB assessment • PBT: Not applicable. • vPvB: Not applicable.

(Contd. on page 3)

US

Printing date 11/29/2016

Reviewed on 09/02/2015

Trade name: MC-CLEAR 100

(Contd. of page 2)

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:			
540-88-5	tert-butyl acetate		
28182-81-2	Hexane, 1,6-diisocyanato-, homopolymer		
53880-05-0	Homopolymer of IPDI		
	methyl amyl ketone		
64742-95-6	Solvent naphtha (petroleum), light arom.		
4098-71-9	isophorone di-isocyanate	0.1-1%%	

4 First-aid measures

· Description of first aid measures

· General information: Immediately remove any clothing soiled by the product.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- · After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

No further relevant information available.

5 *Fire-fighting measures*

- · Extinguishing media
- · Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

6 Accidental release measures

- *Personal precautions, protective equipment and emergency procedures Wear protective equipment. Keep unprotected persons away.*
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.

• *Methods and material for containment and cleaning up:* Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

- *Ensure adequate ventilation.*
- · Reference to other sections

See Section 7 for information on safe handling.

(Contd. on page 4)

[•] US

(Contd. of page 3)

Safety Data Sheet acc. to OSHA HCS

Printing date 11/29/2016

Reviewed on 09/02/2015

Trade name: MC-CLEAR 100

See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

· Handling:

- **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.
- Information about protection against explosions and fires: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- \cdot Further information about storage conditions:
- Keep receptacle tightly sealed. Store in cool, dry conditions in well sealed receptacles.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

· Components with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituents have no known exposure limits.

540-88-5 tert-butyl acetate PEL Long-term value: 950 mg/m³, 200 ppm REL Long-term value: 950 mg/m³, 200 ppm TLV Short-term value: 712 mg/m³, 150 ppm Long-term value: 238 mg/m³, 50 ppm 110-43-0 methyl amyl ketone PEL Long-term value: 465 mg/m³, 100 ppm REL Long-term value: 465 mg/m³, 100 ppm TLV Long-term value: 233 mg/m³, 50 ppm 4098-71-9 isophorone di-isocyanate REL Short-term value: 0.18 mg/m³, 0.02 ppm Long-term value: 0.045 mg/m³, 0.005 ppm Skin TLV Long-term value: 0.045 mg/m³, 0.005 ppm • Additional information: The lists that were valid during the creation were used as basis. (Contd. on page 5)

uge 5)

Printing date 11/29/2016

Reviewed on 09/02/2015

Trade name: MC-CLEAR 100

(Contd. of page 4)

- · Exposure controls
- · Personal protective equipment:

• General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin.

· Breathing equipment:

During mixing, handling and application: Splash goggles. Full protective clothing. Gloves (impervious). Wear suitable respiratory equipment. When air concentrations are not known (or above the TLV), an air-supplied respirator is required. Refer to OSHA Respiratory Protection Standard (29 CFR 1910.134). In presence of air movement, air-purifying (cartridge type) respirators are not the best protection but can be used, if you replaced them frequently. Change cartridges after 8h max or less due to their low warning properties. When in a confined space wear MSHA/NIOSH approved self-contained breathing apparatus or equivalent and full protective gear.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation • Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

9 Physical and chemical properties · Information on basic physical and chemical properties · General Information · Appearance: Form: Fluid Color: Clear/Milky · Odor: Aromatic · Odor threshold: Not determined. Not determined. · *pH-value*: · Change in condition Melting point/Melting range: Undetermined. (Contd. on page 6) US

US

Safety Data Sheet acc. to OSHA HCS

Printing date 11/29/2016

Reviewed on 09/02/2015

Trade name: MC-CLEAR 100

	(Contd. of page 5
Boiling point/Boiling range:	97 °C (207 °F)
· Flash point:	15 °C (59 °F)
Flammability (solid, gaseous):	Not applicable.
Ignition temperature:	
Decomposition temperature:	Not determined.
Auto igniting:	Product is not selfigniting.
Danger of explosion:	Product is not explosive. However, formation of explosive air/vapo mixtures are possible.
Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	41 hPa (31 mm Hg)
• Density at 20 •C (68 •F):	0.95-1.01 g/cm ³ (7.928-8.428 lbs/gal)
Relative density	Not determined.
· Vapor density	Not determined.
Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/wate	e r): Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Other information	No further relevant information available.

10 Stability and reactivity

• *Reactivity* No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- *Incompatible materials:* No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects

• Acute toxicity:

· LD/LC50 values that are relevant for classification:		
64742-95-6 Solvent naphtha (petroleum), light arom.		
Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)
		(Contd. on page 7)

Printing date 11/29/2016

Reviewed on 09/02/2015

Trade name: MC-CLEAR 100

			l. of page 6)
822-06-0	hexameth	ylene-di-isocyanate	
Oral	LD50	738 mg/kg (rat)	
Dermal	LD50	593 mg/kg (rat)	
· Primary i	rritant eff	ect:	
\cdot on the ski	n: Irritant	t to skin and mucous membranes.	
• on the eye	e: Irritatin	g effect.	
 Sensitizat 			
		le through inhalation.	
		le through skin contact.	
		gical information:	
	ict shows t	the following dangers according to internally approved calculation methods for prepa	irations:
Harmful			
Irritant			
The prodi	ict can cai	use inheritable damage.	
· Carcinog	enic categ	ories	
· IARC (In	ternationa	al Agency for Research on Cancer)	
1330-20	-7 xylene		3
14808-60	-7 Quartz	: (SiO2)	1
100-41	-4 ethylbe	enzene	2B
· NTP (Nat	tional Tox	icology Program)	
14808-60	-7 Quartz	: (SiO2)	K
· OSHA-Ca	а (Оссира	tional Safety & Health Administration)	
None of th	he ingredie	ents is listed.	

12 Ecological information

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:
- Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

- Danger to drinking water if even small quantities leak into the ground.
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- · Other adverse effects No further relevant information available.

13 Disposal considerations

- · Waste treatment methods
- · Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 8)

(Contd. of page 7)

Reviewed on 09/02/2015

Safety Data Sheet acc. to OSHA HCS

Trade name: MC-CLEAR 100

Printing date 11/29/2016

Uncleaned packagings:
Recommendation: Disposal must be made according to official regulations.

Transport information	
UN-Number	1111262
DOT, ADR, IMDG, IATA	UN1263
UN proper shipping name	Deline
DOT ADR	Paint 1263 Paint
IMDG, IATA	PAINT
Transport hazard class(es)	
DOT	
Class	3 Flammable liquids
Label	3
ADR, IMDG, IATA	
Class Label	3 Flammable liquids 3
Packing group DOT, ADR, IMDG, IATA	II
Environmental hazards: Marine pollutant:	No
Special precautions for user	Warning: Flammable liquids
Danger code (Kemler):	33
EMS Number:	<i>F-E</i> , <u><i>S-E</i></u>
Stowage Category	В
Transport in bulk according to Annex A MARPOL73/78 and the IBC Code	II of Not applicable.
Transport/Additional information:	
- •	
DOT Quantity limitations	On passenger aircraft/rail: 5 L On cargo aircraft only: 60 L
ADR	
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml

Printing date 11/29/2016

Reviewed on 09/02/2015

Trade name: MC-CLEAR 100

(Contd. of page 8)

· IMDG · Limited quantities (LQ) · Excepted quantities (EQ)	1L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml	
· UN "Model Regulation":	UN 1263 PAINT, 3, II	

15 Regulatory information

 \cdot Safety, health and environmental regulations/legislation specific for the substance or mixture \cdot Sara

· Section 355 (extremely hazardous substances):

4098-71-9 isophorone di-isocyanate

· Section 313 (Specific toxic chemical listings):

4098-71-9 isophorone di-isocyanate

95-63-6 1,2,4-trimethylbenzene

822-06-0 hexamethylene-di-isocyanate

1330-20-7 xylene

100-41-4 ethylbenzene

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

· Proposition 65

· Chemicals known to cause cancer:

14808-60-7 Quartz (SiO2)

100-41-4 ethylbenzene

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

1330-20-7 xylene

100-41-4 ethylbenzene

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

 \cdot NIOSH-Ca (National Institute for Occupational Safety and Health)

14808-60-7 Quartz (SiO2)

• GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS). (Contd. on page 10)

I

D

US

Safety Data Sheet acc. to OSHA HCS

Printing date 11/29/2016

Reviewed on 09/02/2015

Trade name: MC-CLEAR 100

(Contd. of pag	şe 9)
Hazard pictograms	
GHS02 GHS07 GHS08	
011502 011507 011508	
· Signal word Danger	
· Hazard-determining components of labeling:	
Hexane, 1,6-diisocyanato-, homopolymer	
Solvent naphtha (petroleum), light arom.	
isophorone di-isocyanate	
hexamethylene-di-isocyanate	
· Hazard statements	
H225 Highly flammable liquid and vapor.	
H315 Causes skin irritation.	
H319 Causes serious eye irritation.	
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
H317 May cause an allergic skin reaction.	
H340 May cause genetic defects.	
H350 May cause cancer.	
H335 May cause respiratory irritation.	
· Precautionary statements	
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.	
P241 Use explosion-proof electrical/ventilating/lighting/equipment.	
P284 [In case of inadequate ventilation] wear respiratory protection.	
P261 Avoid breathing dust/fume/gas/mist/vapors/spray	
P280 Wear protective gloves / eye protection / face protection.	
P240 Ground/bond container and receiving equipment.	
P242 Use only non-sparking tools.	
P243 Take precautionary measures against static discharge.	
P264 Wash thoroughly after handling.	
P271 Use only outdoors or in a well-ventilated area.	
P272 Contaminated work clothing must not be allowed out of the workplace.	
P201Obtain special instructions before use.P202Do not handle until all safety precautions have been read and understood.	
	tor
P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with was shower.	iei/
P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if pres	sont
and easy to do. Continue rinsing.	eni
P321 Specific treatment (see on this label).	
P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.	
<i>P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.</i>	
<i>P312 Call a POISON CENTER/doctor if you feel unwell.</i>	
P363 Wash contaminated clothing before reuse.	
P308+P313 IF exposed or concerned: Get medical advice/attention.	
<i>P333+P313</i> If skin irritation or rash occurs: Get medical advice/attention.	
<i>P337+P313</i> If eye irritation persists: Get medical advice/attention.	
P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.	
P362+P364 Take off contaminated clothing and wash it before reuse.	
P405 Store locked up.	
P403+P233 Store in a well-ventilated place. Keep container tightly closed.	
P403+P235 Store in a well-ventilated place. Keep cool.	
(Contd. on page	: 11)

Printing date 11/29/2016

Reviewed on 09/02/2015

Trade name: MC-CLEAR 100

P501

(Contd. of page 10) Dispose of contents/container in accordance with local/regional/national/international regulations.

· National regulations:

• Additional classification according to Decree on Hazardous Materials: Carcinogenic hazardous material group III (dangerous).

· Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: HS REG.DEPART.REG.SS
- · Date of preparation / last revision 11/29/2016 / -
- · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Resp. Sens. 1: Respiratory sensitisation – Category 1 Skin Sens. 1: Skin sensitisation - Category 1 Muta. 1B: Germ cell mutagenicity - Category 1B Carc. 1B: Carcinogenicity – Category 1B STOT SE 3: Specific target organ toxicity (single exposure) – Category 3