Printing date 06/07/2018

Reviewed on 06/07/2018

## **1** Identification

- · Product identifier
- · Trade name: POLYFLEX 205
- · Article number: WP205B.XX
- $\cdot$  Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Wasser Corporation 4118 B PL NW, Suite B Auburn, WA 98001, US Phone 253-850-2967
- · Information department: Product safety department
- Emergency telephone number: EMERGENCY PHONE NUMBERS: USA and Canada: 1-800 424-9300 International: 1-703 527-3887

### 2 Hazard(s) identification

· Classification of the substance or mixture

STOT RE 1 H372 Causes damage to organs through prolonged or repeated exposure.

- · Label elements
- · GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).
- · Hazard pictograms



· Signal word Danger

- Hazard-determining components of labeling: Talc (Mg3H2(SiO3)4)
   Hazard statements
- H372 Causes damage to organs through prolonged or repeated exposure.
- · Precautionary statements
- Keep out of reach from children.

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

- P264 Wash thoroughly after handling.
- P270 Do not eat, drink or smoke when using this product.

P314 Get medical advice/attention if you feel unwell.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)



(Contd. on page 2)

Printing date 06/07/2018

Reviewed on 06/07/2018

(Contd. of page 1)

Trade name: POLYFLEX 205

- · Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

### 3 Composition/information on ingredients

· Chemical characterization: Mixtures

- Description: Mixture of the substances listed below with nonhazardous additions.
- · Dangerous components:

14807-96-6 Talc (Mg3H2(SiO3)4)

30-60%

### 4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- $\cdot$  Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

# **5** Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents:
- CO2, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

### **6** Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

- Dispose contaminated material as waste according to item 13.
- · Reference to other sections
- See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

(Contd. on page 3)

Printing date 06/07/2018

Reviewed on 06/07/2018

#### Trade name: POLYFLEX 205

(Contd. of page 2)

#### 7 Handling and storage

- Precautions for safe handling No special precautions are necessary if used correctly.
- · Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- Specific end use(s) No further relevant information available.

#### 8 Exposure controls/personal protection

- · Additional information about design of technical systems: No further data; see item 7.
- · Control parameters
- Components with limit values that require monitoring at the workplace:
- The product does not contain any relevant quantities of materials with critical values that have to be monitored at the workplace.
- Additional information: The lists that were valid during the creation were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Wash hands before breaks and at the end of work. Store protective clothing separately.
- · Breathing equipment:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation  $\cdot$  *Material of gloves* 

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)

Printing date 06/07/2018

Reviewed on 06/07/2018

(Contd. of page 3)

### Trade name: POLYFLEX 205

· Eye protection:



Tightly sealed goggles

#### 9 Physical and chemical properties · Information on basic physical and chemical properties · General Information · Appearance: Form: Fluid Color: Various colors · Odor: Light · Odor threshold: Not determined. · pH-value: Not determined. · Change in condition Melting point/Melting range: Undetermined. **Boiling point/Boiling range:** Undetermined. 94 °C (201.2 °F) · Flash point: · Flammability (solid, gaseous): Not applicable. · Decomposition temperature: Not determined. • Auto igniting: Product is not selfigniting. · Danger of explosion: Product does not present an explosion hazard. · Explosion limits: Not determined. Lower: Upper: Not determined. Not determined. · Vapor pressure: • Density at 20 °C (68 °F): 1.24 g/cm<sup>3</sup> (10.3478 lbs/gal) · Relative density Not determined. · Vapor density Not determined. · Evaporation rate Not determined. · Solubility in / Miscibility with Water:

 Solubility in / Miscibility with
 Not miscible or difficult to mix.

 Water:
 Not miscible or difficult to mix.

 Partition coefficient (n-octanol/water): Not determined.

 Viscosity:
 Not determined.

 Dynamic:
 Not determined.

 Kinematic:
 Not determined.

 VOC content:
 0 %

 0 g/l / 0 lb/gl

 · Other information
 No further relevant information available.

(Contd. on page 5)

Printing date 06/07/2018

Reviewed on 06/07/2018

Trade name: POLYFLEX 205

(Contd. of page 4)

### **10 Stability and reactivity**

- *Reactivity* No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

#### **11 Toxicological information**

· Information on toxicological effects

• Acute toxicity:

#### · LD/LC50 values that are relevant for classification:

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative		>10.2 mg/l (rat)

#### · Primary irritant effect:

• on the skin: No irritant effect.

• on the eye: No irritating effect.

• Sensitization: No sensitizing effects known.

· Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations:

#### · Carcinogenic categories

· IARC (International Agency for Research on Cancer)		
	Talc (Mg3H2(SiO3)4)	3
7631-86-9	silicon dioxide, chemically prepared	3
1330-20-7	xylene	3
· NTP (National Toxicology Program)		
None of the ingredients is listed.		
· OSHA-Ca (Occupational Safety & Health Administration)		
None of the ingredients is listed.		

## **12 Ecological information**

· Toxicity

- · Aquatic toxicity: No further relevant information available.
- · Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- · Additional ecological information:

· General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Printing date 06/07/2018

Reviewed on 06/07/2018

(Contd. of page 5)

Trade name: POLYFLEX 205

· Results of PBT and vPvB assessment

• **PBT:** Not applicable.

• **vPvB:** Not applicable.

 $\cdot$  Other adverse effects No further relevant information available.

# **13 Disposal considerations**

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

· Recommendation: Disposal must be made according to official regulations.

UN-Number	
DOT, ADR, ADN, IMDG, IATA	Void
UN proper shipping name DOT, ADR, ADN, IMDG, IATA	Void
Transport hazard class(es)	
DOT, ADR, ADN, IMDG, IATA Class	Void
Packing group DOT, ADR, IMDG, IATA	Void
Environmental hazards: Marine pollutant:	No
Special precautions for user	Not applicable.
Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
UN "Model Regulation":	Void

## **15 Regulatory information**

 $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara

· Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

1344-28-1 aluminium oxide

1330-20-7 xylene

· TSCA (Toxic Substances Control Act):

All ingredients are listed.

(Contd. on page 7)

US -

Ι

A4

A4

## Safety Data Sheet acc. to OSHA HCS

Printing date 06/07/2018

· Proposition 65

Reviewed on 06/07/2018

Trade name: POLYFLEX 205

	(Contd. of page 6)

• Chemicals known to cause cancer: None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

· Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

1330-20-7 xylene

· TLV (Threshold Limit Value established by ACGIH)

Talc (Mg3H2(SiO3)4)

aluminium oxide

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger

• *Hazard-determining components of labeling: Talc (Mg3H2(SiO3)4)* 

· Hazard statements

H372 Causes damage to organs through prolonged or repeated exposure.

· Precautionary statements

P260 Do not breathe dust/fume/gas/mist/vapors/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P314 Get medical advice/attention if you feel unwell.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department

· Date of preparation / last revision 06/07/2018 / -

Abbreviations and acronyms:
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods

(Contd. on page 8)

<sup>·</sup> Contact: HS REG.DEPART.REG.SS

(Contd. of page 7)

US

# Safety Data Sheet acc. to OSHA HCS

Printing date 06/07/2018

Reviewed on 06/07/2018

#### Trade name: POLYFLEX 205

DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit STOT RE 1: Specific target organ toxicity (repeated exposure) - Category 1

Printing date 06/07/2018

Reviewed on 03/03/2017

### **1** Identification

- · Product identifier
- · Trade name: CATALYST FOR POLYFLEX 205
- · Article number: WP205A.0
- $\cdot$  Details of the supplier of the safety data sheet

• Manufacturer/Supplier: Wasser Corporation 4118 B PL NW, Suite B Auburn, WA 98001, US Phone 253-850-2967

· Information department: Product safety department

• Emergency telephone number: EMERGENCY PHONE NUMBERS: USA and Canada: 1-800 424-9300 International: 1-703 527-3887

### 2 Hazard(s) identification

· Classification of the substance or mixture

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Carc. 2 H351 Suspected of causing cancer.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

#### · Label elements

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger

· Hazard-determining components of labeling: 4,4'-methylenediphenyl diisocyanate methylenediphenyl diisocyanate · Hazard statements H315 Causes skin irritation. H319 Causes serious eye irritation. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H317 May cause an allergic skin reaction. H351 Suspected of causing cancer. H335 May cause respiratory irritation. H373 May cause damage to organs through prolonged or repeated exposure. · Precautionary statements Keep out of reach from children. P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood.

(Contd. on page 2)

<sup>-</sup> US

Printing date 06/07/2018

Reviewed on 03/03/2017

## Trade name: CATALYST FOR POLYFLEX 205

	(Contd. of page 1)
P260	Do not breathe dust/fume/gas/mist/vapors/spray.
P264	Wash thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P284	[In case of inadequate ventilation] wear respiratory protection.
P302+P352	If on skin: Wash with plenty of water.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present
	and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P312	Call a poison center/doctor if you feel unwell.
P321	Specific treatment (see on this label).
P314	Get medical advice/attention if you feel unwell.
P362+P364	Take off contaminated clothing and wash it before reuse.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P342+P311	If experiencing respiratory symptoms: Call a poison center/doctor.
P363	Wash contaminated clothing before reuse.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



· HMIS-ratings (scale 0 - 4)

HEALTH\*2FIRE1FIRE7REACTIVITY0

 $\cdot$  Other hazards

· Results of PBT and vPvB assessment

- · **PBT:** Not applicable.
- · vPvB: Not applicable.

# 3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

U	•		
101-68-8	4,4'-methylenediphenyl diisocyanate	10-30%	
26447-40-5	methylenediphenyl diisocyanate	10-30%	

(Contd. on page 3)

Printing date 06/07/2018

Reviewed on 03/03/2017

#### Trade name: CATALYST FOR POLYFLEX 205

(Contd. of page 2)

### 4 First-aid measures

· Description of first aid measures

· General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

- In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed
- No further relevant information available.

#### **5** Fire-fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Use fire fighting measures that suit the environment.
- Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters
- · Protective equipment: No special measures required.

#### **6** Accidental release measures

- · Personal precautions, protective equipment and emergency procedures Not required.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:
- Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.
- · Reference to other sections
- See Section 7 for information on safe handling.
- See Section 8 for information on personal protection equipment.
- See Section 13 for disposal information.

#### 7 Handling and storage

- · Precautions for safe handling Ensure good ventilation/exhaustion at the workplace.
- Information about protection against explosions and fires: No special measures required.
- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: No special requirements.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep receptacle tightly sealed.

(Contd. on page 4)

US

Printing date 06/07/2018

Reviewed on 03/03/2017

Trade name: CATALYST FOR POLYFLEX 205

(Contd. of page 3)

• Specific end use(s) No further relevant information available.

### 8 Exposure controls/personal protection

• Additional information about design of technical systems: No further data; see item 7.

· Control parameters

#### · Components with limit values that require monitoring at the workplace:

The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

#### 101-68-8 4,4'-methylenediphenyl diisocyanate

PEL Ceiling limit value: 0.2 mg/m<sup>3</sup>, 0.02 ppm

REL Long-term value: 0.05 mg/m<sup>3</sup>, 0.005 ppm Ceiling limit value: 0.2\* mg/m<sup>3</sup>, 0.02\* ppm \*10-min

TLV Long-term value: 0.051 mg/m<sup>3</sup>, 0.005 ppm

• Additional information: The lists that were valid during the creation were used as basis.

#### · Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing. Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the eyes and skin.

#### · Breathing equipment:

During mixing, handling and application: Splash goggles. Full protective clothing. Gloves (impervious). Wear suitable respiratory equipment. When air concentrations are not known (or above the TLV), an air-supplied respirator is required. Refer to OSHA Respiratory Protection Standard (29 CFR 1910.134). In presence of air movement, air-purifying (cartridge type) respirators are not the best protection but can be used, if you replaced them frequently. Change cartridges after 8h max or less due to their low warning properties. When in a confined space wear MSHA/NIOSH approved self-contained breathing apparatus or equivalent and full protective gear.

· Protection of nand



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the

chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation  $\cdot$  *Material of gloves* 

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 5)

Printing date 06/07/2018

Reviewed on 03/03/2017

(Contd. of page 4)

### Trade name: CATALYST FOR POLYFLEX 205

• Eye protection:

· Other information



Tightly sealed goggles

#### **9** Physical and chemical properties · Information on basic physical and chemical properties · General Information · Appearance: Form: Fluid Color: Light brown · Odor: Light · Odor threshold: Not determined. · pH-value: Not determined. · Change in condition Melting point/Melting range: Undetermined. 208 °C (406.4 °F) **Boiling point/Boiling range:** 212 °C (413.6 °F) · Flash point: · Flammability (solid, gaseous): Not applicable. · Ignition temperature: 520 °C (968 °F) · Decomposition temperature: Not determined. · Auto igniting: Product is not selfigniting. · Danger of explosion: Product does not present an explosion hazard. · Explosion limits: Lower: 0.4 Vol % Upper: 0.0 Vol % · Vapor pressure: Not determined. • Density at 20 °C (68 °F): 1.13 g/cm<sup>3</sup> (9.42985 lbs/gal) · Relative density Not determined. · Vapor density Not determined. · Evaporation rate Not determined. · Solubility in / Miscibility with Water: Not miscible or difficult to mix. · Partition coefficient (n-octanol/water): Not determined. · Viscosity: Dynamic: Not determined. Kinematic: Not determined. **VOC** content: 0.00 %

0.0 g/l / 0.00 lb/gl

No further relevant information available.

(Contd. on page 6)

Printing date 06/07/2018

Reviewed on 03/03/2017

Trade name: CATALYST FOR POLYFLEX 205

(Contd. of page 5)

### **10 Stability and reactivity**

- *Reactivity* No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

#### **11 Toxicological information**

- · Information on toxicological effects
- Acute toxicity:
- · LD/LC50 values that are relevant for classification:

#### 101-68-8 4,4'-methylenediphenyl diisocyanate

Oral LD50 2,200 mg/kg (mouse)

- · Primary irritant effect:
- on the skin: Irritant to skin and mucous membranes.
- on the eye: Irritating effect.
- Sensitization: Sensitization possible through inhalation. Sensitization possible through skin contact.
- · Additional toxicological information:

The product shows the following dangers according to internally approved calculation methods for preparations: Harmful

Irritant

#### · Carcinogenic categories

· IARC (International Agency for Research on Cancer)

101-68-8 4,4'-methylenediphenyl diisocyanate

· NTP (National Toxicology Program)

None of the ingredients is listed.

#### · OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

## **12 Ecological information**

- · Toxicity
- · Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- · Behavior in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.
- $\cdot$  Additional ecological information:
- · General notes:
- Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.

(Contd. on page 7)

3

Printing date 06/07/2018

Reviewed on 03/03/2017

(Contd. of page 6)

### Trade name: CATALYST FOR POLYFLEX 205

- **vPvB:** Not applicable.
- Other adverse effects No further relevant information available.

### **13 Disposal considerations**

· Waste treatment methods

· Recommendation:

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packagings:

• Recommendation: Disposal must be made according to official regulations.

14 Transport information	
· UN-Number · DOT, ADR, ADN, IMDG, IATA	Void
· UN proper shipping name · DOT, ADR, ADN, IMDG, IATA	Void
· Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA · Class	Void
· Packing group · DOT, ADR, IMDG, IATA	Void
· Environmental hazards: · Marine pollutant:	No
· Special precautions for user	Not applicable.
• Transport in bulk according to Annex I MARPOL73/78 and the IBC Code	II of Not applicable.
· UN "Model Regulation":	Void

### **15 Regulatory information**

- $\cdot$  Safety, health and environmental regulations/legislation specific for the substance or mixture  $\cdot$  Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

101-68-8 4,4'-methylenediphenyl diisocyanate

· TSCA (Toxic Substances Control Act):

- All ingredients are listed.
- · Proposition 65

 $\cdot$  Chemicals known to cause cancer:

None of the ingredients is listed.

(Contd. on page 8)

US -

Printing date 06/07/2018

Reviewed on 03/03/2017

(Contd. of page 7)

Trade name: CATALYST FOR POLYFLEX 205

· Chemicals known to	cause reproductive	toxicity for females:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity for males:

None of the ingredients is listed.

 $\cdot$  Chemicals known to cause developmental toxicity:

None of the ingredients is listed.

· Carcinogenic categories

· EPA (Environmental Protection Agency)

101-68-8 4,4'-methylenediphenyl diisocyanate

D, CBD

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients is listed.

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

• *GHS label elements* The product is classified and labeled according to the Globally Harmonized System (GHS). • *Hazard pictograms* 



· Signal word Danger

• Signal wora L	anger	
	nining components of labeling: Prediphenyl diisocyanate	
	enyl diisocyanate	
· Hazard staten		
H315 Causes		
H319 Causes	serious eye irritation.	
	use allergy or asthma symptoms or breathing difficulties if inhaled.	
	ise an allergic skin reaction.	
H351 Suspecte	ed of causing cancer.	
Н335 Мау саг	ise respiratory irritation.	
•	use damage to organs through prolonged or repeated exposure.	
• Precautionary		
P201	Obtain special instructions before use.	
P202	Do not handle until all safety precautions have been read and understood.	
P260	Do not breathe dust/fume/gas/mist/vapors/spray.	
P264	Wash thoroughly after handling.	
P271	Use only outdoors or in a well-ventilated area.	
P272	Contaminated work clothing must not be allowed out of the workplace.	
P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P284	[In case of inadequate ventilation] wear respiratory protection.	
P302+P352	If on skin: Wash with plenty of water.	
P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
P305+P351+	P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present	
D200 + D212	and easy to do. Continue rinsing.	
P308+P313	<i>IF exposed or concerned: Get medical advice/attention.</i>	
P312 P321	Call a poison center/doctor if you feel unwell.	
P321 P314	Specific treatment (see on this label). Get medical advice/attention if you feel unwell.	
1 314	Get meatcat davice/attention if you jeet unwett.	

Printing date 06/07/2018

Reviewed on 03/03/2017

#### Trade name: CATALYST FOR POLYFLEX 205

	(Contd. of page 8)
P362+P364	Take off contaminated clothing and wash it before reuse.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P337+P313	If eye irritation persists: Get medical advice/attention.
P342+P311	If experiencing respiratory symptoms: Call a poison center/doctor.
P363	Wash contaminated clothing before reuse.
P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.
P501	Dispose of contents/container in accordance with local/regional/national/international
	regulations.

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

### **16 Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- · Department issuing SDS: Product safety department
- · Contact: HS REG.DEPART.REG.SS
- · Date of preparation / last revision 06/07/2018 / -
- Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods DOT: US Department of Transportation IATA: International Air Transport Association ACGIH: American Conference of Governmental Industrial Hygienists EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) NFPA: National Fire Protection Association (USA) HMIS: Hazardous Materials Identification System (USA) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative NIOSH: National Institute for Occupational Safety OSHA: Occupational Safety & Health TLV: Threshold Limit Value PEL: Permissible Exposure Limit REL: Recommended Exposure Limit Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Resp. Sens. 1: Respiratory sensitisation - Category 1 Skin Sens. 1: Skin sensitisation - Category 1 Carc. 2: Carcinogenicity – Category 2 STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 US