

TACOMA NARROWS BRIDGE

TACOMA, WASHINGTON

PROJECT DATE
2015

SUBSTRATE
STEEL



COMPANY

Washington Department of Transportation

PROJECT NAME

Bridge Recoating

CONTRACTORS

/

SYSTEMS

Primer

MC-Zinc
3.0 - 5.0 Mils DFT

Intermediate

MC-Ferrox B
3.0 - 5.0 Mils DFT

Topcoat

MC-Ferrox A
2.0 - 5.0 Mils DFT

THE CHALLENGE

The Tacoma Narrows Bridge spans the windswept waters of Puget Sound, where salt air, driving rain, and constant moisture create an aggressive corrosion environment for exposed steel. To protect this critical infrastructure, Wasser specified and supplied a high-performance moisture-cured urethane system tailored for long-term durability in marine conditions. Following proper surface preparation and abrasive blasting to achieve the required profile and cleanliness.

WHY WASSER

MC-Miozinc was applied to provide both barrier protection and galvanic defense. This zinc-rich primer incorporates micaceous iron oxide (MIO) for enhanced film strength and moisture resistance, forming a dense, corrosion-inhibiting foundation directly bonded to the steel substrate. Over the primer, MC-Ferrox B was installed as the intermediate coat to build film thickness and reinforce the protective barrier. This layer enhances impact resistance and provides additional shielding against moisture intrusion and chl

OUR SOLUTION

Together, this three-coat moisture-cured system performs exceptionally well in high-humidity environments, allowing for reliable curing even in less-than-ideal conditions. The result is a durable, tightly sealed coating system that protects the bridge's structural steel from corrosion, reduces maintenance frequency, and ensures continued performance against the demanding weather patterns of Western Washington.