



## 1. Product and Company Identification

<b>Material name</b>	<b>Polyflex 511 Tack Coat</b>
<b>Version #</b>	00
<b>Revision date</b>	01/01/2021
<b>CAS #</b>	Mixture
<b>Product use</b>	Pavement Sealing and Preservation
<b>Manufacturer</b>	
<b>Manufacturer:</b>	Wasser Technologies
<b>Address:</b>	4118 B Place NW Suite B Auburn, WA 98001 USA

## 2. Hazards Identification

<b>Emergency overview</b>	May cause central nervous system depression. May cause irritation to the respiratory system.
<b>Potential health effects</b>	
<b>Routes of exposure</b>	Inhalation.
<b>Eyes</b>	Contact with eyes may cause irritation. Molten material will produce thermal burns.
<b>Skin</b>	Irritating to skin.
<b>Inhalation</b>	Prolonged inhalation may be harmful. May cause sensitization of susceptible persons by inhalation of aerosol or dust.
<b>Ingestion</b>	Expected to be a low ingestion hazard. Irritating to mouth, throat, and stomach.
<b>Signs and symptoms</b>	Irritation of eyes and mucous membranes. Dermatitis. Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting.
<b>Potential environmental effects</b>	Ecological injuries are not known or expected under normal use.

## 3. Composition / Information on Ingredients

<b>Hazardous components</b>	<b>CAS #</b>	<b>Percent</b>
ASPHALT	8052-42-4	40 - 95
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC	64742-52-5	0 - 15
<b>Non-hazardous components</b>	<b>CAS #</b>	<b>Percent</b>
MINERAL FILLER	Mixture	0 - 45
VULCANIZED RUBBER COMPOUND	Mixture	0 - 20
POLYESTER FIBERS	25038-59-9	0 - 10
STYRENE/ISOPRENE COPOLYMER	25038-32-8	0 - 15
ETHYLENE/BUTADIENE COPOLYMER	66070-58-4	0 - 10
SBS BLOCK COPOLYMER	Proprietary	0 - 10

## 4. First Aid Measures

### First aid procedures

#### Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation develops and persists.

#### Skin contact

In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Thoroughly wash (or discard) clothing and shoes before reuse.

#### Inhalation

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. Call a physician if symptoms develop or persist.

#### Ingestion

Rinse mouth. Do not induce vomiting. Call a POISON CENTER or doctor/physician if you feel unwell. Do not use mouth-to-mouth method if victim ingested the substance.

### Notes to physician

In case of ingestion, the decision of whether or not to induce vomiting should be made by the attending physician. Certain pre-existing conditions may make workers particularly susceptible to the effects of this chemical: asthma, allergies, impaired pulmonary function.

### General advice

Discard any shoes or clothing items that cannot be decontaminated.

## 5. Fire Fighting Measures

### Flammable properties

Container may explode in heat of fire. Not flammable by OSHA criteria.

### Extinguishing media

#### Suitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO<sub>2</sub>). Addition of water or foam to the fire may cause frothing.

#### Unsuitable extinguishing media

Do not use a solid water stream as it may scatter and spread fire.

### Protection of firefighters

#### Specific hazards arising from the chemical

Development of hazardous combustion gases or vapours possible in the event of a fire. The following may develop: Acrolein.

#### Protective equipment and precautions for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Structural firefighters protective clothing will only provide limited protection.

### Fire fighting equipment/instructions

In case of fire and/or explosion do not breathe fumes. ALWAYS stay away from tanks engulfed in flame. Fight fire from maximum distance or use unmanned hose holders or monitor nozzles. In the event of fire, cool tanks with water spray. By fire, toxic gases may be formed (CO<sub>x</sub>, NO<sub>x</sub>). Keep run-off water out of sewers and water sources. Dike for water control.

### Specific methods

In the event of fire and/or explosion do not breathe fumes. In the event of fire, cool tanks with water spray. Use water spray to cool unopened containers.

### Hazardous combustion products

Oxides of carbon and nitrogen Sulfur dioxide.

## 6. Accidental Release Measures

### Personal precautions

Keep unnecessary personnel away. Ventilate closed spaces before entering them. Do not touch or walk through spilled material. Wear appropriate protective equipment and clothing during clean-up.

### Environmental precautions

Runoff or release to sewer, waterway or ground is forbidden.

### Methods for containment

ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Stop the flow of material, if this is without risk. Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable.

### Methods for cleaning up

Dike far ahead of spill for later disposal. Collect and dispose of spillage as indicated in section 13 of the MSDS.

Never return spills in original containers for re-use.

## 7. Handling and Storage

### Handling

The product is non-combustible. If heated, irritating vapors may be formed. Wash hands after handling. Observe good industrial hygiene practices. Do not use in areas without adequate ventilation.

### Storage

Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a well-ventilated place. Keep the container tightly closed and dry. Store in a closed container away from incompatible materials.

## 8. Exposure Controls / Personal Protection

### Occupational exposure limits

#### US. ACGIH Threshold Limit Values

Components	Type	Value	Form
ASPHALT (8052-42-4)	TWA	0.5 mg/m3	Inhalable fraction.
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (64742-52-5)	TWA	5 mg/m3	Inhalable fraction.

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
DISTILLATES (PETROLEUM), HYDROTREATED HEAVY NAPHTHENIC (64742-52-5)	PEL	5 mg/m3	Mist.
		2000 mg/m3	
		500 ppm	

### Engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

### Personal protective equipment

<b>Eye / face protection</b>	Wear safety glasses; chemical goggles (if splashing is possible). Wear chemical goggles; face shield (if handling molten material).
<b>Skin protection</b>	Wear suitable protective clothing and eye/face protection. Use of an impervious apron is recommended.
<b>Respiratory protection</b>	When workers are facing concentrations above the exposure limit they must use appropriate certified respirators.
<b>General hygiene considerations</b>	When using do not smoke.

## 9. Physical & Chemical Properties

<b>Appearance</b>	Solid.
<b>Physical state</b>	Liquid.
<b>Form</b>	Solid.
<b>Color</b>	Black. Dark brown
<b>Odor</b>	Product is a black, semi-solid with a burnt tar odor.
<b>Odor threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Vapor pressure</b>	Not available.
<b>Vapor density</b>	Not available.
<b>Boiling point</b>	> 800 °F (> 426.7 °C)
<b>Melting point/Freezing point</b>	220 °F estimated
<b>Solubility (water)</b>	Not available.
<b>Specific gravity</b>	1 - 1.9
<b>Relative density</b>	Not available.
<b>Flash point</b>	> 400 °F (> 204.4 °C)
<b>Flammability limits in air, upper, % by volume</b>	Not available.
<b>Flammability limits in air, lower, % by volume</b>	Not available.
<b>Auto-ignition temperature</b>	> 700 °F (> 371.1 °C)
<b>Percent volatile</b>	< 1 %
<b>Other data</b>	
<b>Density</b>	Not Available
<b>Flammability class</b>	Combustible IIIB estimated

## 10. Chemical Stability & Reactivity Information

<b>Chemical stability</b>	Material is stable under normal conditions.
<b>Conditions to avoid</b>	Strong oxidizing agents.
<b>Incompatible materials</b>	Incompatible with oxidizing agents.
<b>Hazardous decomposition products</b>	Upon decomposition, product emits acrid dense smoke with carbon dioxide, carbon monoxide, trace oxides of nitrogen and sulfur, and water.
<b>Possibility of hazardous reactions</b>	Hazardous polymerization does not occur.

## 11. Toxicological Information

<b>Chronic effects</b>	Prolonged inhalation may be harmful. May cause eczema-like skin disorders (dermatitis).
<b>Carcinogenicity</b>	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.
<b>Skin corrosion/irritation</b>	Defats the skin. Causes irritation.

## 12. Ecological Information

<b>Ecotoxicity</b>	This product has no known eco-toxicological effects.
<b>Environmental effects</b>	Ecological injuries are not known or expected under normal use. An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
<b>Persistence and degradability</b>	Not available.

## 13. Disposal Considerations

<b>Waste codes</b>	Not applicable.
<b>Disposal instructions</b>	Dispose of contents/container in accordance with local/regional/national/international regulations.

## 14. Transport Information

<b>Further information</b>	If shipped above 212 deg F: "UN3257, Elevated Temperature Liquid, n.o.s., 9, PG III"
----------------------------	--

## 15. Regulatory Information

<b>US federal regulations</b>	This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
-------------------------------	--

### Drug Enforcement Administration (DEA). List 2, Essential Chemicals (21 CFR 1310.02(b) and 1310.04(f)(2))

Not regulated

### DEA Essential Chemical Code Number

Not regulated

### Drug Enforcement Administration (DEA). List 1 & 2 Exempt Chemical Mixtures (21 CFR 1310.12(c))

Not regulated

### DEA Exempt Chemical Mixtures Code Number

Not regulated

### CERCLA (Superfund) reportable quantity

None

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

<b>Hazard categories</b>	Immediate Hazard - Yes Delayed Hazard - Yes Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No
--------------------------	--

<b>Section 302 extremely hazardous substance</b>	No
--	----

<b>Section 311 hazardous chemical</b>	No
---------------------------------------	----

### Inventory status

<b>Country(s) or region</b>	<b>Inventory name</b>	<b>On inventory (yes/no)*</b>
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes

Country(s) or region	Inventory name	On inventory (yes/no)*
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

\*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

**State regulations** WARNING: This product contains a chemical known to the State of California to cause cancer.

**US - California Proposition 65 - CRT: Listed date/Carcinogenic substance**

ASPHALT (CAS 8052-42-4) Listed: January 1, 1990 Carcinogenic.

**US - New Jersey RTK - Substances: Listed substance**

ASPHALT (CAS 8052-42-4) Listed.

**US - Pennsylvania RTK - Hazardous Substances: Listed substance**

ASPHALT (CAS 8052-42-4) Listed.

**US - Pennsylvania RTK - Hazardous Substances: Special hazard**

ASPHALT (CAS 8052-42-4) Special hazard.

## 16. Other Information

**Further information**

HMIS® is a registered trade and service mark of the NPCA.

**HMIS® ratings**

Health: 1\*  
Flammability: 1  
Physical hazard: 0

**NFPA ratings**

Health: 1  
Flammability: 1  
Instability: 0

**Disclaimer**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

**Issue date**

Not available.