



Material Safety Data Sheet

Date Originated: 01/01/2021

Page: 1

NFPA 	HCS Risk Phrases	Protective Clothing 
	HCS CLASS: Toxic. HCS CLASS: Severely irritating substance. HCS CLASS: Target organ effects. HCS CLASS: Flammable liquid having a flash point lower than 37.8°C (100°F).	

Section 1. Chemical Product and Company Identification

Product Name

Polyflex WP102A Rapid-Thane H.G. White

Synonym

WP102A.7H

Manufacturer

SUPPLIER:
 Wasser Technologies
 4118 B PL NW, Suite B
 Auburn, WA 98001, US
 Phone# 253-850-2967

Chemical Family

Not applicable.

In case of Emergency

EMERGENCY PHONE NUMBERS:
 USA and Canada: 1-800 424-9300
 International: 1-703 527-3887

Section 2. Composition and Information on Ingredients

Name	CAS #	% by Weight	TLV/PEL	LC ₅₀ /LD ₅₀
Asparticacid Ester	136210-32-7	10-30	Not available.	ORAL (LD50): Acute: 2000 mg/kg [Rat]. DERMAL (LD50): Acute: 2000 mg/kg [Rat].
Titanium oxide	13463-67-7	10-30	TWA: 10 (mg/m ³) from ACGIH INHALATION	ORAL (LD50): Acute: 24000 mg/kg [Rat]. DERMAL (LD50): Acute: 10000 mg/kg [Rabbit].
Aspartic Ester	Not available	5-10	Not available.	ORAL (LD50): Acute: 2000 mg/kg [Rat].
Tert Butyl Acetate	540-88-5	5-10	TWA: 200 (ppm) from ACGIH (TLV) TWA: 200 (ppm) from OSHA	ORAL (LD50): Acute: 4100 mg/kg [Rat]. DERMAL (LD50): Acute: 2000 mg/kg [Rabbit].
Di(2-ethylhexyl) phthalate	117-81-7	1-5		
Cyclohexanemethanamine, 1,3,3-trimethyl-N-(2-methylpropylidene-5-(2-methylpropylidene) amino)-	54914-37-3	1-5	Not available.	ORAL (LD50): Acute: 4150 mg/kg [Rat]. DERMAL (LD50): Acute: 5000 mg/kg [Rabbit].
Methyl n-amyl ketone	110-43-0	1-5	TWA: 50 (ppm) from ACGIH (TLV), TWA: 100 (ppm) from OSHA (PEL)	DERMAL (LD50): Acute: 12600 mg/kg [Rabbit]. VAPOR (LC50): Acute: 3000 ppm 4 hour(s) [Rat].
Parachlorobenzotrifluoride	98-56-6	1-5	CEIL: 25 (ppm)	DERMAL (LD50): Acute: 2700 mg/kg [Rabbit]. VAPOR (LC50): Acute: 4479 ppm 4 hour(s) [Rat].
Xylenes	1330-20-7	0-1	TWA: 100 STEL: 150 (ppm) from OSHA (PEL)	DERMAL (LD50): Acute: 2000 mg/kg [Rabbit]. VAPOR (LC50): Acute: 6700 ppm 4 hour(s) [Rat].

Material Safety Data Sheet

Product Name: Polyflex WP102A Rapid-Thane
H.G. White

Page: 2

Section 3. Hazards Identification

Routes of Entry: Inhalation. Skin contact (absorption). Eye contact. Ingestion.

Potential Acute Health Effects

Eyes: Liquid or spray mist may severely irritate eyes. Inflammation of the eye is characterized by burning, redness, watering, and itching.

Skin: This product may severely irritate skin upon contact. Harmful if absorbed through the skin. Skin inflammation is characterized by itching, scaling, reddening, or, occasionally, blistering.

Ingestion: Harmful if swallowed. Irritation or chemical burns of the mouth, pharynx, esophagus and stomach can develop following ingestion of this product. Even small amounts of liquid aspirated into the lungs during ingestion or vomiting may cause pulmonary injury and possibly death.

Inhalation: Harmful if inhaled (irritant). Over-exposure by inhalation of the vapors/spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath. Exposure can cause nausea, headaches and vomiting. Massive exposure can cause unconsciousness and death.

Potential Chronic Health Effects

Eyes: Repeated or prolonged contact with spray mist may produce chronic eye irritation.

Skin: Repeated skin exposure can produce local skin destruction, or dermatitis.

Ingestion: May be fatal if swallowed.

Inhalation: Repeated or prolonged inhalation of vapors/spray mist may lead to chronic respiratory irritation.

Other chronic effects on Humans

The substance is toxic to mucous membranes, upper respiratory tract, lungs, blood, kidney, liver. Exposure may cause asthma, dermatitis and pulmonary oedema; effects may be delayed.

Section 4. First Aid Measures

Eye Contact Check for and remove any contact lenses. DO NOT use an eye ointment. IMMEDIATELY flush eyes with running water for at least 15 minutes, keeping eyelids open. Seek medical attention.

Skin Contact Wash gently and thoroughly the contaminated skin with running water and non-abrasive soap. Rinse with plenty of running water (15-30 minutes). If irritation persists, seek medical attention.

Hazardous Skin Contact If the chemical gets onto the clothed portion of the body, remove the contaminated clothes as quickly as possible, protecting your own hands and body. Place the person under shower. Wash gently and thoroughly the contaminated skin with running water and non abrasive soap. Be particularly careful to clean folds, crevices, creases and groin. Rinse with plenty of running water (15 to 30 minutes). Seek medical attention.

Inhalation Allow the person to rest in a well ventilated area. If symptoms persist, seek medical advice immediately (show the label when possible).

Hazardous Inhalation Evacuate the person to a safe area as soon as possible. Loosen tight clothing around the person's neck and waist. If the person is not breathing, administer mouth-to-mouth resuscitation. Warning: It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation if the inhaled material is toxic, infectious or corrosive. Seek medical attention.

Ingestion DO NOT induce vomiting. Have conscious person drink several glasses of water or milk. Seek immediate medical attention.

Hazardous Ingestion DO NOT induce vomiting. Have conscious person drink several glasses of water or milk. Loosen tight clothing such as a collar, tie, belt or waistband. Never give an unconscious person anything to ingest. Even small amounts of liquid aspirated into lungs during ingestion or from vomiting may cause mild to severe pulmonary injury and possibly death. If breathing is difficult, administer oxygen. If the person is not breathing, administer mouth-to-mouth resuscitation. WARNING: It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation when the material is toxic, infectious or corrosive. Avoid mouth-to-mouth contact by using mouth guards or shields. Seek immediate medical attention.


Material Safety Data Sheet

Product Name: Polyflex WP102A Rapid-Thane
H.G. White

Page: 3

Section 5. Fire and Explosion Data

Flammability of the Product	Flammable.
Auto-Ignition Temperature	The lowest known value is 240°C (464°F) (Cyclohexan emethanamine, 1,3,3-trimethyl-N-(2-methylpropylidene-5-(2-methylpropylidene) amino)-).
Flash Points	The lowest known value is CLOSED CUP: 4.4°C (39.9°F). (Tert Butyl Acetate)
Flammable Limits	The greatest known range is LOWER: 0.9% UPPER: 10.5% (Parachlorobenzotrifluoride)
Products of Combustion	Carbon oxides (CO, CO2), and other unidentified, possibly toxic compounds.
Fire Hazards in Presence of Various Substances	Flammable in presence of open flames and sparks.
Explosion Hazards in Presence of Various Substances	Risks of explosion of the product in presence of mechanical impact: Not available. Risks of explosion of the product in presence of static discharge: YES.
Fire Fighting Media and Instructions	SMALL FIRE: Use DRY chemicals, CO2, water spray or foam. LARGE FIRE: Use water spray or fog. Never direct a water jet in the container in order to prevent any splashing of the product which could cause spreading of the fire. Cool the containers with water spray or fog in order to prevent pressure build-up, autoignition or explosion. Firefighters should be equipped with self-contained breathing apparatus to protect against toxic and irritating fumes. During a fire, irritating, toxic gases may be generated by thermal decomposition or combustion.
Special Remarks on Fire Hazards	Vapor may travel considerable distance to source of ignition and flash back. When heated to decomposition it emits toxic fumes.
Special Remarks on Explosion Hazards	Container explosion may occur under fire conditions or when heated (due to pressure build-up). Vapor forms explosive mixture with air between upper and lower flammable limits.



Section 6. Accidental Release Measures

Small Spill	Absorb with an inert material and put the spilled material in an appropriate waste disposal. Wear suitable protective clothing and proper respirator.
Large Spill	Poisonous, flammable liquid, insoluble or very slightly soluble in water. Ventilate. Eliminate all sources of ignition. Wear full protective equipment, including respiratory equipment during clean-up. Stop leak if without risk. DO NOT touch spilled material. Prevent entry into storm or sanitary sewers, lakes, rivers, streams or public waterways. Call for assistance on disposal.

Material Safety Data Sheet

Product Name: Polyflex WP102A Rapid-Thane H.G.
White

Page: 4

Section 7. Handling and Storage

Precautions	Keep locked up and out of reach of children. Manipulate in a well ventilated area. In case of insufficient ventilation, wear suitable respiratory equipment. Do not breathe gas/fumes/vapor/spray. Avoid contact with skin and eyes. Contact lenses should not be worn when working with chemicals because they may contribute to the severity of an eye injury. Keep away from foodstuff, drinks and tobacco. Eating, drinking and smoking should be prohibited in area where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Ensure that eyewash station and safety shower is proximal to the work-station location. In case of accident or if you feel unwell, seek medical advice immediately (show the label when possible). Individuals with respiratory problems (asthma, chronic bronchitis), or allergic to solvents or epoxys, should avoid any contact with this product. Ground all equipment containing material (during handling, mixing and spraying).
Storage	Keep away from heat. Keep away from sources of ignition. Keep away from food, drink and animal feeding stuffs. Keep away from incompatibles. Keep container tightly closed and dry. Keep in a cool, well-ventilated place.

Section 8. Exposure Controls/Personal Protection

Engineering Controls	Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash station and safety shower are proximal to the work-station location. Do air monitoring if possible.
Personal Protection	Splash goggles. Synthetic apron. Gloves (impervious). In case of insufficient ventilation, wear suitable respiratory equipment. Be sure to use a MSHA/NIOSH approved respirator or equivalent.
Personal Protection in Case of a Large Spill	Splash goggles. Gloves (impervious to chemicals). Full suit. Boots. Wear appropriate respirator when ventilation is inadequate.

Section 9. Physical and Chemical Properties

Physical state and appearance	Liquid.	Odor	Aromatic.
Molecular Weight	Not applicable.	Taste	Not available.
pH (1% soln/water)	Not applicable.	Color	White.
Boiling Point	The lowest known value is 139°C (282.2°F) (Parachlorobenzotrifluoride). Weighted average: 187.76°C (370°F)	Odor Threshold	The highest known value is 0.05 ppm (Methyl n-amyl ketone)
Melting Point	May start to solidify at -12°C (10.4°F)	Evaporation rate	0.4 (Methyl n-amyl ketone).compared to Butyl acetate = 1
Critical Temperature	Not available.	Viscosity	Not available.
Specific Gravity	1.43 (Water = 1)	Water/Oil Dist. Coeff.	Not available.
Vapor Pressure	The highest known value is 34 mm of Hg (@ 20°C) (Tert Butyl Acetate). Weighted average: 18.34 mm of Hg (@ 20°C)	Ionicity (in Water)	Not available.
Vapor Density	The highest known value is 16 (Air = 1) (Di(2-ethylhexyl) phthalate). Weighted average: 10.54 (Air = 1)	Dispersion Properties	Is not dispersed in water.
Volatility	25% (v/v). 17% (w/w).	Solubility	Insoluble in water.

Section 10. Stability and Reactivity Data

Stability	The product is stable.
Instability Temperature	Not available.
Conditions of Instability	No additional remarks.
Incompatibility with various substances	Reactive with oxidizing agents.
Corrosivity	Not considered to be corrosive for glass and metals according to our data base.
Special Remarks on Reactivity	No additional remarks.

Material Safety Data Sheet

Product Name: Polyflex WP102A Rapid-Thane
H.G. White

Page: 5

Section 11. Toxicological Information

Routes of Entry	Inhalation. Skin contact (absorption). Eye contact. Ingestion.
Toxicity to Animals	See: Section II
Chronic Effects on Humans	The substance is toxic to mucous membranes, upper respiratory tract, lungs, blood, kidney, liver. Exposure may cause asthma, dermatitis and pulmonary oedema; effects may be delayed.
Other Toxic Effects on Humans	Dangerous in case of skin contact (irritant, permeator), of eye contact (irritant), of ingestion, of inhalation.
Special Remarks on Toxicity to Animals	Embryofetotoxic in animal studies (Xylene). Testicular damage in animal. An experimental teratogen (Di(2-ethylhexyl) phthalate). IARC Group 2B carcinogen - possibly carcinogenic to humans (Titanium dioxide).
Special Remarks on Chronic Effects on Humans	Reports have associated repeated and prolonged occupational exposure to solvents with permanent brain and nervous system damage, and other systemic effects. Intentional misuse by deliberately concentrating and inhaling vapors may be harmful or fatal.
Special Remarks on other Toxic Effects on Humans	Exposure can cause nausea, headache and vomiting. Moderately toxic and narcotic in high concentrations.

Section 12. Ecological Information

Ecotoxicity	Not available.
BOD5 and COD	Not available.
Products of Biodegradation	Not available.
Toxicity of the Products of Biodegradation	Not available.
Special Remarks on the Products of Biodegradation	No additional remarks.

Section 13. Disposal Considerations

Waste Disposal	In accordance with municipal, provincial and federal regulations. Consult your local or regional authorities. Empty containers must be handled with care due to product residue. Do not heat or cut empty containers with electric or gas torch.
----------------	--

Section 14. Transport Information

DOT Classification	DOT CLASS 3: Flammable liquid PG: II
DOT Identification number	UN1263: Paint
Special Provisions for Transport	No additional remark.
DOT (Pictograms)	



Material Safety Data Sheet

Product Name: Polyflex WP102A Rapid-Thane
H.G. White

Page: 6

Section 15. Other Regulatory Information and Pictograms

Other Regulations TSCA (Toxic Substance Control Act): All components of this product are listed on the TSCA Inventory. OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Other Classifications WHMIS (Canada)

DSCL (EEC)

Hazardous Material Information System (U.S.A.)

Health Hazard	3
Fire Hazard	3
Reactivity	0
Personal Protection	

National Fire Protection Association (U.S.A.)

Health



Fire Hazard

Reactivity

Specific hazard

WHMIS (Canada) (Pictograms)

DSCL (Europe) (Pictograms)

TDG (Canada) (Pictograms)

ADR (Europe) (Pictograms)

Protective Clothing (Pictograms)



Section 16. Other Information

References Manufacturer's MSDS, RTESC, NIOSH, CCOHS.

Other Special Considerations Individuals with respiratory problems (asthma, chronic bronchitis) should avoid any contact with this product.

Validated on 01/01/2021.

Printed 01/01/2021.

EMERGENCY PHONE NUMBERS:

USA and Canada: 1-800 424-9300

International: 1-703 527-3887

Notice to Reader

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.