

Safety Data Sheet

acc. to OSHA HCS

Printing date

Reviewed on 01/01/2021

Trade name: THINNER

(Contd. of page 9)

*H335 May cause respiratory irritation.***Precautionary statements**

- P210 *Keep away from heat/sparks/open flames/hot surfaces. - No smoking.*
- P241 *Use explosion-proof electrical/ventilating/lighting/equipment.*
- P261 *Avoid breathing dust/fume/gas/mist/vapors/spray*
- P280 *Wear protective gloves / eye protection / face protection.*
- P280 *Wear protective gloves.*
- P280 *Wear eye protection / face protection.*
- P240 *Ground/bond container and receiving equipment.*
- P242 *Use only non-sparking tools.*
- P243 *Take precautionary measures against static discharge.*
- P264 *Wash thoroughly after handling.*
- P271 *Use only outdoors or in a well-ventilated area.*
- P201 *Obtain special instructions before use.*
- P202 *Do not handle until all safety precautions have been read and understood.*
- P303+P361+P353 *IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.*
- P305+P351+P338 *If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
- P321 *Specific treatment (see on this label).*
- P304+P340 *IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.*
- P312 *Call a poison center/doctor if you feel unwell.*
- P308+P313 *IF exposed or concerned: Get medical advice/attention.*
- P332+P313 *If skin irritation occurs: Get medical advice/attention.*
- P337+P313 *If eye irritation persists: Get medical advice/attention.*
- P370+P378 *In case of fire: Use for extinction: CO2, powder or water spray.*
- P362+P364 *Take off contaminated clothing and wash it before reuse.*
- P405 *Store locked up.*
- P403+P233 *Store in a well-ventilated place. Keep container tightly closed.*
- P403+P235 *Store in a well-ventilated place. Keep cool.*
- P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Product safety department

· **Contact:** HS REG.DEPART.REG.SS

· **Date of preparation / last revision** 01/01/2021 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Acute Tox. 4: Acute toxicity, Hazard Category 4

Skin Irrit. 2: Skin corrosion/irritation, Hazard Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation, Hazard Category 2A

(Contd. on page 11)

Safety Data Sheet
acc. to OSHA HCS

Printing date 01/01/2021

Reviewed on 01/01/2021

Trade name: THINNER

Carc. 2: Carcinogenicity, Hazard Category 2
STOT SE 3: Specific target organ toxicity - Single exposure, Hazard Category 3

(Contd. of page 10)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/01/2021

Reviewed on 01/01/2021

1 Identification

- **Product identifier**
- **Trade name:** MC-THINNER 100
- **Article number:** W43.0
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Wasser Technologies
4118 B PL NW, Suite B
Auburn, WA 98001, US
Phone 253-850-2967
- **Information department:** Product safety department
- **Emergency telephone number:**
EMERGENCY PHONE NUMBERS:
USA and Canada: 1-800 424-9300
International: 1-703 527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**



Flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Health hazard

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.

Asp. Tox. 1 H304 May be fatal if swallowed and enters airways.



Acute Tox. 4 H332 Harmful if inhaled.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02



GHS07



GHS08

- **Signal word** *Danger*

- **Hazard-determining components of labeling:**

Solvent naphtha (petroleum), light arom.

methyl amyl ketone

- **Hazard statements**

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H340 May cause genetic defects.

H350 May cause cancer.

H304 May be fatal if swallowed and enters airways.

(Contd. on page 2)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/01/2021

Reviewed on 01/01/2021

Trade name: MC-THINNER 100

(Contd. of page 1)

· Precautionary statements

Keep out of reach from children.

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P280 Wear protective gloves / eye protection / face protection.

P240 Ground/bond container and receiving equipment.

P233 Keep container tightly closed.

P242 Use only non-sparking tools.

P243 Take precautionary measures against static discharge.

P271 Use only outdoors or in a well-ventilated area.

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P301+P310 If swallowed: Immediately call a poison center/doctor.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312 Call a poison center/doctor if you feel unwell.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P331 Do NOT induce vomiting.

P370+P378 In case of fire: Use for extinction: CO2, powder or water spray.

P405 Store locked up.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Classification system:

· NFPA ratings (scale 0 - 4)



Health = 2

Fire = 2

Reactivity = 0

· HMIS-ratings (scale 0 - 4)



Health = *2

Fire = 2

Reactivity = 0

· Other hazards

· Results of PBT and vPvB assessment

· PBT: Not applicable.

· vPvB: Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures

· Description: Mixture of the substances listed below with nonhazardous additions.

· Dangerous components:

64742-95-6	Solvent naphtha (petroleum), light arom.	60-100%%
110-43-0	methyl amyl ketone	10-30%%

4 First-aid measures

· Description of first aid measures

· After inhalation: Supply fresh air; consult doctor in case of complaints.

· After skin contact: Immediately rinse with water.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/01/2021

Reviewed on 01/01/2021

Trade name: MC-THINNER 100

(Contd. of page 2)

- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Do not allow product to reach sewage system or any water course.
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

US

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/01/2021

Reviewed on 01/01/2021

Trade name: MC-THINNER 100

(Contd. of page 3)

8 Exposure controls/personal protection

· **Additional information about design of technical systems:** No further data; see item 7.

· **Control parameters**

· **Components with limit values that require monitoring at the workplace:**

110-43-0 methyl amyl ketone

PEL Long-term value: 465 mg/m³, 100 ppm

REL Long-term value: 465 mg/m³, 100 ppm

TLV Long-term value: 233 mg/m³, 50 ppm

· **Additional information:** The lists that were valid during the creation were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Store protective clothing separately.

· **Breathing equipment:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use respiratory protective device that is independent of circulating air.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form: Fluid

Color: Transparent

· **Odor:** Aromatic

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/01/2021

Reviewed on 01/01/2021

Trade name: MC-THINNER 100

(Contd. of page 4)

· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	151 °C (304 °F)
· Flash point:	41 °C (106 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	450 °C (842 °F)
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits: Lower:	0.7 Vol %
Upper:	7.5 Vol %
· Vapor pressure at 20 °C (68 °F):	5 hPa (4 mm Hg)
· Density at 20 °C (68 °F):	0.86 g/cm ³ (7.177 lbs/gal)
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity: Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content: Organic solvents:	99.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity**
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· LD/LC50 values that are relevant for classification:

64742-95-6 Solvent naphtha (petroleum), light arom.
--

Oral	LD50	>6800 mg/kg (rat)
------	------	-------------------

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/01/2021

Reviewed on 01/01/2021

Trade name: MC-THINNER 100

(Contd. of page 5)

Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)
110-43-0 methyl amyl ketone		
Oral	LD50	1670 mg/kg (rat)
Dermal	LD50	12600 mg/kg (rabbit)

- **Primary irritant effect:**

- **on the skin:** No irritant effect.

- **on the eye:** No irritating effect.

- **Sensitization:** No sensitizing effects known.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Carcinogenic.

The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.

- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.

- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.

- **vPvB:** Not applicable.

- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packaging:**

- **Recommendation:** Disposal must be made according to official regulations.

US

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS



Printing date 01/01/2021

Reviewed on 01/01/2021

Trade name: MC-THINNER 100

(Contd. of page 6)

14 Transport information

<ul style="list-style-type: none"> · UN-Number · DOT, ADR, IMDG, IATA 	UN1263
<ul style="list-style-type: none"> · UN proper shipping name · DOT · ADR · IMDG, IATA 	Paint related material 1263 Paint related material PAINT RELATED MATERIAL
<ul style="list-style-type: none"> · Transport hazard class(es) · DOT 	<div style="text-align: center;">  <p>3</p> </div>
<ul style="list-style-type: none"> · Class · Label 	3 Flammable liquids 3
<ul style="list-style-type: none"> · ADR, IMDG, IATA 	<div style="text-align: center;">  <p>3</p> </div>
<ul style="list-style-type: none"> · Class · Label 	3 Flammable liquids 3
<ul style="list-style-type: none"> · Packing group · DOT, ADR, IMDG, IATA 	III
<ul style="list-style-type: none"> · Environmental hazards: · Marine pollutant: 	No
<ul style="list-style-type: none"> · Special precautions for user · Danger code (Kemler): · EMS Number: 	Warning: Flammable liquids 30 F-E,S-E
<ul style="list-style-type: none"> · Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code 	Not applicable.
<ul style="list-style-type: none"> · Transport/Additional information: · DOT · Quantity limitations 	On passenger aircraft/rail: 60 L On cargo aircraft only: 220 L
<ul style="list-style-type: none"> · ADR · Excepted quantities (EQ) 	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<ul style="list-style-type: none"> · IMDG · Limited quantities (LQ) · Excepted quantities (EQ) 	5L Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
<ul style="list-style-type: none"> · UN "Model Regulation": 	UN1263, Paint related material, 3, III

US

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/01/2021

Reviewed on 01/01/2021

Trade name: MC-THINNER 100

(Contd. of page 7)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- Sara

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
-----------	--------

100-41-4	ethylbenzene
----------	--------------

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-41-4	ethylbenzene
----------	--------------

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene	I
-----------	--------	---

100-41-4	ethylbenzene	D
----------	--------------	---

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02

GHS07

GHS08

· **Signal word** *Danger*

· **Hazard-determining components of labeling:**

Solvent naphtha (petroleum), light arom.

methyl amyl ketone

· **Hazard statements**

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H340 May cause genetic defects.

H350 May cause cancer.

H304 May be fatal if swallowed and enters airways.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/01/2021

Reviewed on 01/01/2021

Trade name: MC-THINNER 100

(Contd. of page 8)

P280	Wear protective gloves / eye protection / face protection.
P240	Ground/bond container and receiving equipment.
P233	Keep container tightly closed.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P271	Use only outdoors or in a well-ventilated area.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P301+P310	If swallowed: Immediately call a poison center/doctor.
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P312	Call a poison center/doctor if you feel unwell.
P308+P313	IF exposed or concerned: Get medical advice/attention.
P331	Do NOT induce vomiting.
P370+P378	In case of fire: Use for extinction: CO ₂ , powder or water spray.
P405	Store locked up.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- **National regulations:**

- **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Product safety department

- **Contact:** HS REG.DEPART.REG.SS

- **Date of preparation / last revision** 01/01/2021 / -

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

Flam. Liq. 3: Flammable liquids, Hazard Category 3

Acute Tox. 4: Acute toxicity, Hazard Category 4

Muta. 1B: Germ cell mutagenicity, Hazard Category 1B

Carc. 1B: Carcinogenicity, Hazard Category 1B

Asp. Tox. 1: Aspiration hazard, Hazard Category 1

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/20/2017

Reviewed on 03/20/2017

1 Identification

- **Product identifier**
- **Trade name:** MC-THINNER XMT
- **Article number:** W45.00
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
 Wasser Technologies
 4118 B PL NW, Suite B
 Auburn, WA 98001, US
 Phone 253-850-2967
- **Information department:** Product safety department
- **Emergency telephone number:**
 EMERGENCY PHONE NUMBERS:
 USA and Canada: 1-800 424-9300
 International: 1-703 527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**
 Flam. Liq. 2 H225 Highly flammable liquid and vapor.
 Skin Irrit. 2 H315 Causes skin irritation.
 Eye Irrit. 2A H319 Causes serious eye irritation.
- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS02 GHS07

- **Signal word** *Danger*
- **Hazard statements**
 H225 Highly flammable liquid and vapor.
 H315 Causes skin irritation.
 H319 Causes serious eye irritation.
- **Precautionary statements**
 Keep out of reach from children.
 P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 P241 Use explosion-proof electrical/ventilating/lighting/equipment.
 P280 Wear protective gloves / eye protection / face protection.
 P280 Wear protective gloves / eye protection / face protection.
 P240 Ground/bond container and receiving equipment.
 P233 Keep container tightly closed.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P264 Wash thoroughly after handling.
 P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P321 Specific treatment (see on this label).

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/20/2017

Reviewed on 03/20/2017

Trade name: MC-THINNER XMT

(Contd. of page 1)

P332+P313 If skin irritation occurs: Get medical advice/attention.
 P337+P313 If eye irritation persists: Get medical advice/attention.
 P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.
 P362+P364 Take off contaminated clothing and wash it before reuse.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- **Classification system:**
- **NFPA ratings (scale 0 - 4)**



- **HMIS-ratings (scale 0 - 4)**

HEALTH	2	Health = 2
FIRE	3	Fire = 3
REACTIVITY	0	Reactivity = 0

- **Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of the substances listed below with nonhazardous additions.

· **Dangerous components:**

98-56-6	4-chloro-alpha,alpha,alpha-trifluorotoluene	60-100%%
540-88-5	tert-butyl acetate	10-30%%

4 First-aid measures

- **Description of first aid measures**
- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/20/2017

Reviewed on 03/20/2017

Trade name: MC-THINNER XMT

(Contd. of page 2)

- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Precautions for safe handling** No special precautions are necessary if used correctly.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

540-88-5 tert-butyl acetate

PEL	Long-term value: 950 mg/m ³ , 200 ppm
REL	Long-term value: 950 mg/m ³ , 200 ppm
TLV	Short-term value: 712 mg/m ³ , 150 ppm Long-term value: 238 mg/m ³ , 50 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.

(Contd. on page 4)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/20/2017

Reviewed on 03/20/2017

Trade name: MC-THINNER XMT

(Contd. of page 3)

- **Exposure controls**

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

- **Breathing equipment:**

During mixing, handling and application: Splash goggles. Full protective clothing. Gloves (impervious). Wear suitable respiratory equipment. When air concentrations are not known (or above the TLV), an air-supplied respirator is required. Refer to OSHA Respiratory Protection Standard (29 CFR 1910.134). In presence of air movement, air-purifying (cartridge type) respirators are not the best protection but can be used, if you replaced them frequently. Change cartridges after 8h max or less due to their low warning properties. When in a confined space wear MSHA/NIOSH approved self-contained breathing apparatus or equivalent and full protective gear.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form: Fluid

Color: Colourless

- **Odor:** Solvent-like

- **Odor threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range: Undetermined.

Boiling point/Boiling range: 97 °C (207 °F)

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/20/2017

Reviewed on 03/20/2017

Trade name: MC-THINNER XMT

(Contd. of page 4)

· Flash point:	15 °C (59 °F)
· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	
Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapor mixtures are possible.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure at 20 °C (68 °F):	41 hPa (31 mm Hg)
· Density at 20 °C (68 °F):	1.26 g/cm ³ (10.515 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/20/2017

Reviewed on 03/20/2017

Trade name: MC-THINNER XMT

(Contd. of page 5)

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

1330-20-7	xylene	3
100-41-4	ethylbenzene	2B

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.

- **Behavior in environmental systems:**

- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.

- **Additional ecological information:**

- **General notes:**

Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.

- **Results of PBT and vPvB assessment**

- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**

- **Recommendation:**

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- **Uncleaned packagings:**

- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**

- **DOT, ADR, IMDG, IATA** UN1263

- **UN proper shipping name**

- **DOT** Paint related material
- **ADR** 1263 Paint related material
- **IMDG, IATA** PAINT RELATED MATERIAL

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/20/2017

Reviewed on 03/20/2017

Trade name: MC-THINNER XMT

(Contd. of page 6)

· **Transport hazard class(es)**· **DOT**

· **Class** 3 Flammable liquids
 · **Label** 3

· **ADR, IMDG, IATA**

· **Class** 3 Flammable liquids
 · **Label** 3

· **Packing group**· **DOT, ADR, IMDG, IATA** II· **Environmental hazards:** Not applicable.· **Special precautions for user** Warning: Flammable liquids· **Danger code (Kemler):** 33· **EMS Number:** F-E,S-E· **Stowage Category** B

· **Transport in bulk according to Annex II of
 MARPOL73/78 and the IBC Code** Not applicable.

· **Transport/Additional information:**· **DOT**

· **Quantity limitations** On passenger aircraft/rail: 5 L
 On cargo aircraft only: 60 L

· **ADR**

· **Excepted quantities (EQ)** Code: E2
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 500 ml

· **IMDG**

· **Limited quantities (LQ)** 1L
 · **Excepted quantities (EQ)** Code: E2
 Maximum net quantity per inner packaging: 30 ml
 Maximum net quantity per outer packaging: 500 ml

· **UN "Model Regulation":** UN 1263 PAINT RELATED MATERIAL, 3, II

US

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/20/2017

Reviewed on 03/20/2017

Trade name: MC-THINNER XMT

(Contd. of page 7)

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1330-20-7	xylene
-----------	--------

100-41-4	ethylbenzene
----------	--------------

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

100-41-4	ethylbenzene
----------	--------------

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

1330-20-7	xylene		
-----------	--------	--	--

I

100-41-4	ethylbenzene		
----------	--------------	--	--

D

· **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Danger

· **Hazard statements**

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P280 Wear protective gloves / eye protection / face protection.

P280 Wear protective gloves / eye protection / face protection.

P240 Ground/bond container and receiving equipment.

(Contd. on page 9)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 03/20/2017

Reviewed on 03/20/2017

Trade name: MC-THINNER XMT

(Contd. of page 8)

- P233 *Keep container tightly closed.*
- P242 *Use only non-sparking tools.*
- P243 *Take precautionary measures against static discharge.*
- P264 *Wash thoroughly after handling.*
- P303+P361+P353 *If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.*
- P305+P351+P338 *If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.*
- P321 *Specific treatment (see on this label).*
- P332+P313 *If skin irritation occurs: Get medical advice/attention.*
- P337+P313 *If eye irritation persists: Get medical advice/attention.*
- P370+P378 *In case of fire: Use for extinction: CO₂, powder or water spray.*
- P362+P364 *Take off contaminated clothing and wash it before reuse.*
- P403+P235 *Store in a well-ventilated place. Keep cool.*
- P501 *Dispose of contents/container in accordance with local/regional/national/international regulations.*

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Product safety department

· **Contact:** HS REG.DEPART.REG.SS

· **Date of preparation / last revision** 03/20/2017 / -

· **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

NIOSH: National Institute for Occupational Safety

OSHA: Occupational Safety & Health

TLV: Threshold Limit Value

PEL: Permissible Exposure Limit

REL: Recommended Exposure Limit

Flam. Liq. 2: Flammable liquids – Category 2

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A