

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/01/2026

Reviewed on 01/01/2026

1 Identification

- **Product identifier**
- **Trade name:** MC-TRUEGRIP 100
- **Article number:** W371.XXXX
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Wasser Technologies
3050 Biscayne Blvd., Ste. 302,
Miami, FL 33137
Phone 253-850-2967
- **Information department:** Product safety department
- **Emergency telephone number:**
 EMERGENCY PHONE NUMBERS:
 USA and Canada: 1-800 424-9300
 International: 1-703 527-3887

2 Hazard(s) identification

- **Classification of the substance or mixture**



Flame

Flam. Liq. 2 H225 Highly flammable liquid and vapor.



Health hazard

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Muta. 1B H340 May cause genetic defects.

Carc. 1B H350 May cause cancer.



Skin Sens. 1 H317 May cause an allergic skin reaction.

- **Label elements**

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS02 GHS08

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Talc (Mg₃H₂(SiO₃)₄)

Hexane, 1,6-diisocyanato-, homopolymer

Solvent naphtha (petroleum), light arom.

isophorone di-isocyanate

- **Hazard statements**

H225 Highly flammable liquid and vapor.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/01/2026

Reviewed on 01/01/2026

Trade name: MC-TRUEGRIP 100

(Contd. of page 1)

*H340 May cause genetic defects.**H350 May cause cancer.***· Precautionary statements***Keep out of reach from children.**P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.**P241 Use explosion-proof electrical/ventilating/lighting/equipment.**P284 [In case of inadequate ventilation] wear respiratory protection.**P261 Avoid breathing dust/fume/gas/mist/vapors/spray**P280 Wear protective gloves / eye protection / face protection.**P240 Ground/bond container and receiving equipment.**P233 Keep container tightly closed.**P242 Use only non-sparking tools.**P243 Take precautionary measures against static discharge.**P272 Contaminated work clothing must not be allowed out of the workplace.**P201 Obtain special instructions before use.**P202 Do not handle until all safety precautions have been read and understood.**P303+P361+P353 If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.**P321 Specific treatment (see on this label).**P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.**P363 Wash contaminated clothing before reuse.**P304+P341 If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.**P308+P313 IF exposed or concerned: Get medical advice/attention.**P333+P313 If skin irritation or rash occurs: Get medical advice/attention.**P370+P378 In case of fire: Use for extinction: CO₂, powder or water spray.**P405 Store locked up.**P403+P235 Store in a well-ventilated place. Keep cool.**P501 Dispose of contents/container in accordance with local/regional/national/international regulations.***· Classification system:****· NFPA ratings (scale 0 - 4)**

Health = 2

Fire = 3

Reactivity = 0

· HMIS-ratings (scale 0 - 4)

HEALTH *2 Health = *2

FIRE 3 Fire = 3

REACTIVITY 0 Reactivity = 0

· Other hazards**· Results of PBT and vPvB assessment****· PBT:** Not applicable.**· vPvB:** Not applicable.

3 Composition/information on ingredients

· Chemical characterization: Mixtures**· Description:** Mixture of the substances listed below with nonhazardous additions.**· Dangerous components:**

540-88-5	tert-butyl acetate	10-30%%
14807-96-6	Talc (Mg ₃ H ₂ (SiO ₃) ₄)	5-10%%
110-43-0	methyl amyl ketone	1-5%%
53880-05-0	Homopolymer of IPDI	1-5%%

(Contd. on page 3)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/01/2026

Reviewed on 01/01/2026

Trade name: MC-TRUEGRIP 100

(Contd. of page 2)

28182-81-2	Hexane, 1,6-diisocyanato-, homopolymer	1-5%%
64742-95-6	Solvent naphtha (petroleum), light arom.	1-5%%
13463-67-7	titanium dioxide	0.1-10%%
1333-86-4	Carbon black	0.1-1%%

4 First-aid measures

- **Description of first aid measures**
- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:**
Supply fresh air and to be sure call for a doctor.
In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** If symptoms persist consult doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**
No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:**
CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture** No further relevant information available.
- **Advice for firefighters**
- **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/01/2026

Reviewed on 01/01/2026

Trade name: MC-TRUEGRIP 100

(Contd. of page 3)

Keep respiratory protective device available.

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.
- **Control parameters**

• **Components with limit values that require monitoring at the workplace:**

540-88-5 tert-butyl acetate

PEL	Long-term value: 950 mg/m ³ , 200 ppm
REL	Long-term value: 950 mg/m ³ , 200 ppm
TLV	Short-term value: NIC-712 mg/m ³ , NIC-150 ppm Long-term value: (950) NIC-238 mg/m ³ , (200) NIC-50 ppm

110-43-0 methyl amyl ketone

PEL	Long-term value: 465 mg/m ³ , 100 ppm
REL	Long-term value: 465 mg/m ³ , 100 ppm
TLV	Long-term value: 233 mg/m ³ , 50 ppm

4098-71-9 isophorone di-isocyanate

REL	Short-term value: 0.18 mg/m ³ , 0.02 ppm Long-term value: 0.045 mg/m ³ , 0.005 ppm Skin
TLV	Long-term value: 0.045 mg/m ³ , 0.005 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.

- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
- **Breathing equipment:**
During mixing, handling and application: Splash goggles. Full protective clothing. Gloves (impervious).
Wear suitable respiratory equipment. When air concentrations are not known (or above the TLV), an air-supplied respirator is required. Refer to OSHA Respiratory Protection Standard (29 CFR 1910.134). In presence of air movement, air-purifying (cartridge type) respirators are not the best protection but can be used, if you replaced them frequently. Change cartridges after 8h max or less due to their low warning properties. When in a confined space wear MSHA/NIOSH approved self-contained breathing apparatus or equivalent and full protective gear.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/01/2026

Reviewed on 01/01/2026

Trade name: MC-TRUEGRIP 100

(Contd. of page 4)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

Form:	Fluid
Color:	Various colors
Odor:	Aromatic
Odour threshold:	Not determined.

- **pH-value:** Not determined.

- **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	97 °C (207 °F)

- **Flash point:** 15 °C (59 °F)

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:**

Decomposition temperature: Not determined.

- **Auto igniting:** Product is not selfigniting.

- **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

- **Explosion limits:**

Lower:	Not determined.
Upper:	Not determined.

- **Vapor pressure at 20 °C (68 °F):** 41 hPa (31 mm Hg)

- **Density at 20 °C (68 °F):** 1.57-1.81 g/cm³ (13.102-15.104 lbs/gal)

- **Relative density** Not determined.

- **Vapour density** Not determined.

- **Evaporation rate** Not determined.

- **Solubility in / Miscibility with**

Water: Not miscible or difficult to mix.

- **Partition coefficient (n-octanol/water):** Not determined.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/01/2026

Reviewed on 01/01/2026

Trade name: MC-TRUEGRIP 100

(Contd. of page 5)

- | | |
|----------------------------|--|
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent content: | |
| Solids content: | 82-86 % |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral LD50 >6800 mg/kg (rat)

Dermal LD50 >3400 mg/kg (rab)

Inhalative LC50/4 h >10.2 mg/l (rat)

64741-65-7 Naphtha (petroleum), heavy alkylate

Oral LD50 > 6000 mg/kg (rat)

Dermal LD50 > 3000 mg/kg (rabbit)

Inhalative LC50/4 h > 7.8 mg/l (rat)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.
- **Sensitization:**
Sensitization possible through inhalation.
Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Harmful
Irritant
The product can cause inheritable damage.

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

14807-96-6	Talc (Mg3H2(SiO3)4)	2B
13463-67-7	titanium dioxide	2B
1333-86-4	Carbon black	2B
7631-86-9	silicon dioxide, chemically prepared	3
1330-20-7	xylene	3

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/01/2026

Reviewed on 01/01/2026

Trade name: MC-TRUEGRIP 100

(Contd. of page 6)

100-41-4	ethylbenzene	2B
111-76-2	2-butoxyethanol	3

· **NTP (National Toxicology Program)**

None of the ingredients is listed.

· **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 3 (Self-assessment): extremely hazardous for water
Do not allow product to reach ground water, water course or sewage system, even in small quantities.
Danger to drinking water if even extremely small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1263
- **UN proper shipping name**
- **DOT, IATA** Paint
- **ADR** 1263 Paint
- **IMDG** PAINT
- **Transport hazard class(es)**
- **DOT**
- 
- **Class** 3 Flammable liquids

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/01/2026

Reviewed on 01/01/2026

Trade name: MC-TRUEGRIP 100

(Contd. of page 7)

· Label 3

· ADR, IMDG, IATA



· Class 3 Flammable liquids

· Label 3

· Packing group

· DOT, ADR, IMDG, IATA II

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Warning: Flammable liquids

· Danger code (Kemler): 33

· EMS Number: F-E,S-E

· Stowage Category B

· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code Not applicable.

· Transport/Additional information:

· DOT

· Quantity limitations On passenger aircraft/rail: 5 L
On cargo aircraft only: 60 L

· ADR

· Excepted quantities (EQ) Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

· IMDG

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml

· UN "Model Regulation": UN 1263 PAINT, 3, II

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

· Sara

· Section 355 (extremely hazardous substances):

4098-71-9 isophorone di-isocyanate

· Section 313 (Specific toxic chemical listings):

4098-71-9 isophorone di-isocyanate

95-63-6 1,2,4-trimethylbenzene

872-50-4 N-methyl-2-pyrrolidone

822-06-0 hexamethylene-di-isocyanate

1330-20-7 xylene

100-41-4 ethylbenzene

111-76-2 2-butoxyethanol

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/01/2026

Reviewed on 01/01/2026

Trade name: MC-TRUEGRIP 100

(Contd. of page 8)

• **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

• **Proposition 65**

• **Chemicals known to cause cancer:**

13463-67-7 titanium dioxide

1333-86-4 Carbon black

100-41-4 ethylbenzene

• **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

• **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

• **Chemicals known to cause developmental toxicity:**

872-50-4 N-methyl-2-pyrrolidone

• **Carcinogenic categories**

• **EPA (Environmental Protection Agency)**

1330-20-7 xylene

I

100-41-4 ethylbenzene

D

111-76-2 2-butoxyethanol

NL

• **TLV (Threshold Limit Value established by ACGIH)**

Talc ($Mg_3H_2(SiO_3)_4$)

A4

titanium dioxide

A4

Carbon black

A4

• **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7 titanium dioxide

1333-86-4 Carbon black

• **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

• **Hazard pictograms**



GHS02 GHS08

• **Signal word** Danger

• **Hazard-determining components of labeling:**

Talc ($Mg_3H_2(SiO_3)_4$)

Hexane, 1,6-diisocyanato-, homopolymer

Solvent naphtha (petroleum), light arom.

isophorone di-isocyanate

• **Hazard statements**

H225 Highly flammable liquid and vapor.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H340 May cause genetic defects.

H350 May cause cancer.

• **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P284 [In case of inadequate ventilation] wear respiratory protection.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

(Contd. on page 10)

Safety Data Sheet

acc. to OSHA HCS

Printing date 01/01/2026

Reviewed on 01/01/2026

Trade name: MC-TRUEGRIP 100

(Contd. of page 9)

P280	Wear protective gloves / eye protection / face protection.
P240	Ground/bond container and receiving equipment.
P233	Keep container tightly closed.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P272	Contaminated work clothing must not be allowed out of the workplace.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P303+P361+P353	If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P321	Specific treatment (see on this label).
P342+P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
P363	Wash contaminated clothing before reuse.
P304+P341	If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.
P308+P313	If exposed or concerned: Get medical advice/attention.
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P370+P378	In case of fire: Use for extinction: CO ₂ , powder or water spray.
P405	Store locked up.
P403+P235	Store in a well-ventilated place. Keep cool.
P501	Dispose of contents/container in accordance with local/regional/national/international regulations.

- **National regulations:**

- **Additional classification according to Decree on Hazardous Materials:**

Carcinogenic hazardous material group III (dangerous).

- **Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

- **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Department issuing SDS:** Product safety department

- **Contact:** HS REG.DEPART.REG.SS

- **Date of preparation / last revision** 01/01/2026 / -

- **Abbreviations and acronyms:**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

ACGIH: American Conference of Governmental Industrial Hygienists

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids, Hazard Category 2

Resp. Sens. 1: Sensitisation - Respirat., Hazard Category 1

Skin Sens. 1: Sensitisation - Skin, Hazard Category 1

Muta. 1B: Germ cell mutagenicity, Hazard Category 1B

Carc. 1B: Carcinogenicity, Hazard Category 1B