

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/22/2021

Reviewed on 12/22/2021

1 Identification

- **Product identifier**
- **Trade name:** POLYFLEX 207 GREY RESIN
- **Article number:** WP207B3800
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Wasser Technologies
4118 B PL NW, Suite B
Auburn, WA 98001, US
Phone 253-850-2967
- **Information department:** Product safety department
- **Emergency telephone number:**
EMERGENCY PHONE NUMBERS:
USA and Canada: 1-800 424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**
Skin Sens. 1 H317 May cause an allergic skin reaction.
Carc. 2 H351 Suspected of causing cancer. Route of exposure: Inhalation.
Repr. 1B H360 May damage fertility or the unborn child.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



- **Signal word** Danger
- **Hazard-determining components of labeling:**
tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate
dibutyltin dilaurate
- **Hazard statements**
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer. Route of exposure: Inhalation.
H360 May damage fertility or the unborn child.
- **Precautionary statements**
Keep out of reach from children.
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P261 Avoid breathing dust/fume/gas/mist/vapors/spray
P272 Contaminated work clothing must not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352 If on skin: Wash with plenty of water.
P308+P313 IF exposed or concerned: Get medical advice/attention.
P321 Specific treatment (see on this label).
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P363 Wash contaminated clothing before reuse.
P405 Store locked up.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/22/2021

Reviewed on 12/22/2021

Trade name: **POLYFLEX 207 GREY RESIN**

(Contd. of page 1)

· **Classification system:**· **NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 0

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**

Health = 1

Fire = 0

Reactivity = 0

· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**· **Description:** Mixture of the substances listed below with nonhazardous additions.· **Dangerous components:**

136210-30-5	tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate	30-60%
623-91-6	diethyl fumarate	1-5%
13463-67-7	titanium dioxide	0.1-1%
77-58-7	dibutyltin dilaurate	0.1-1%
1333-86-4	Carbon black	0.1-1%

4 First-aid measures

· **Description of first aid measures**· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.· **After eye contact:** Rinse opened eye for several minutes under running water.· **After swallowing:** If symptoms persist consult doctor.· **Information for doctor:**· **Most important symptoms and effects, both acute and delayed** No further relevant information available.· **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

· **Extinguishing media**· **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.· **Special hazards arising from the substance or mixture** No further relevant information available.· **Advice for firefighters** Not available

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/22/2021

Reviewed on 12/22/2021

Trade name: **POLYFLEX 207 GREY RESIN**

(Contd. of page 2)

· **Protective equipment:** No special measures required.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures** Not required.
- **Environmental precautions:** Do not allow to enter sewers/surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** Keep respiratory protective device available.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No information available.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.
At this time, the other constituents have no known exposure limits.

77-58-7 dibutyltin dilaurate

PEL	Long-term value: 0.1 mg/m ³ as Sn
REL	Long-term value: 0.1 mg/m ³ as Sn, Skin
TLV	Short-term value: 0.2 mg/m ³ Long-term value: 0.1 mg/m ³ as Sn; A4; Skin

1333-86-4 Carbon black

PEL	Long-term value: 3.5 mg/m ³
-----	--

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/22/2021

Reviewed on 12/22/2021

Trade name: **POLYFLEX 207 GREY RESIN**

(Contd. of page 3)

REL	Long-term value: 3.5 mg/m^3 *0.1 in presence of PAHs; See Pocket Guide Apps.A+C
TLV	Long-term value: 3 mg/m^3 *inhalable fraction, A3

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
Use splash goggles, solvent resistant gloves. Long-sleeved clothing ideally made of cotton. A cartridge mask.
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
- **Breathing equipment:**
In the event where the product is sprayed, applied in a method where it can become airborne or when air concentrations are not known (or above the TLV), an air-supplied respirator is required. Refer to OSHA Respiratory Protection Standard (29 CFR 1910.134). In presence of air movement, air-purifying (cartridge type) respirators are not the best protection but can be used, if you replaced them frequently. Change cartridges after 8h max or less due to their low warning properties. When in a confined space wear MSHA/NIOSH approved self-contained breathing apparatus or equivalent and full protective gear ref. SSPC-TU 8.
- **Protection of hands:**



Protective gloves

- The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- **Material of gloves**
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
 - **Penetration time of glove material**
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
 - **Eye protection:** Goggles recommended during refilling.
 - **Body protection:** Protective work clothing

9 Physical and chemical properties

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

Form:	Liquid
Color:	Grey
Odor:	Light
Odor threshold:	Not determined.
- **pH-value:** Not determined.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/22/2021

Reviewed on 12/22/2021

Trade name: **POLYFLEX 207 GREY RESIN**

(Contd. of page 4)

· Change in condition	
Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	Undetermined.
· Flash point:	Not applicable.
· Flammability (solid, gaseous):	Not applicable.
· Decomposition temperature:	Not determined.
· Auto igniting:	Product is not selfigniting.
· Danger of explosion:	Product does not present an explosion hazard.
· Explosion limits:	
Lower:	Not determined.
Upper:	Not determined.
· Vapor pressure:	Not determined.
· Density at 20 °C (68 °F):	1.04 g/cm ³ (8.6788 lbs/gal)
· Relative density	Not determined.
· Vapor density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with	
Water:	Not miscible or difficult to mix.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent separation test	
VOC content:	0.00 % 0.0 g/l / 0.00 lb/gal
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** The product is stable at room temperature.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**
- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** No irritating effect.

(Contd. on page 6)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/22/2021

Reviewed on 12/22/2021

Trade name: **POLYFLEX 207 GREY RESIN**

(Contd. of page 5)

- **Sensitization:** Sensitization possible through skin contact.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

13463-67-7	titanium dioxide	2B
1333-86-4	Carbon black	2B
7631-86-9	silicon dioxide, chemically prepared	3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 2 (Self-assessment): hazardous for water
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· UN-Number	
· DOT, ADR, IMDG, IATA	Void
· UN proper shipping name	
· DOT, ADR, IMDG, IATA	Void

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/22/2021

Reviewed on 12/22/2021

Trade name: **POLYFLEX 207 GREY RESIN**

(Contd. of page 6)

· Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA	
· Class	Void
· Packing group	
· DOT, ADR, IMDG, IATA	Void
· Environmental hazards:	Not applicable.
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	Void

15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
No further relevant information available.
- **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

1344-28-1 aluminium oxide

· **TSCA (Toxic Substances Control Act):**

All components have the value ACTIVE.

· **Hazardous Air Pollutants**

None of the ingredients is listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

13463-67-7 titanium dioxide

1333-86-4 Carbon black

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

None of the ingredients is listed.

· **TLV (Threshold Limit Value)**

titanium dioxide

A4

dibutyltin dilaurate

A4

Carbon black

A4

(Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/22/2021

Reviewed on 12/22/2021

Trade name: **POLYFLEX 207 GREY RESIN**

(Contd. of page 7)

aluminium oxide

A4

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

13463-67-7 titanium dioxide

1333-86-4 Carbon black

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).· **Hazard pictograms**· **Signal word** Danger· **Hazard-determining components of labeling:**

tetraethyl-N,N'-(methylenedicyclohexane-4,1-diyl)bis-DL-aspartate
dibutyltin dilaurate

· **Hazard statements**

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer. Route of exposure: Inhalation.

H360 May damage fertility or the unborn child.

· **Precautionary statements**

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing dust/fume/gas/mist/vapors/spray

P272 Contaminated work clothing must not be allowed out of the workplace.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352 If on skin: Wash with plenty of water.

P308+P313 IF exposed or concerned: Get medical advice/attention.

P321 Specific treatment (see on this label).

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P363 Wash contaminated clothing before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Department issuing SDS:** Product safety department· **Contact:** HS REG.DEPART.REG.SS· **Date of preparation / last revision** 12/22/2021 / -· **Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

VOC: Volatile Organic Compounds (USA, EU)

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

(Contd. on page 9)

Safety Data Sheet
acc. to OSHA HCS

Printing date 12/22/2021

Reviewed on 12/22/2021

Trade name: POLYFLEX 207 GREY RESIN

(Contd. of page 8)

*NIOSH: National Institute for Occupational Safety**OSHA: Occupational Safety & Health**TLV: Threshold Limit Value**PEL: Permissible Exposure Limit**REL: Recommended Exposure Limit**Skin Sens. 1: Skin sensitisation – Category 1**Carc. 2: Carcinogenicity – Category 2**Repr. 1B: Reproductive toxicity – Category 1B*

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/22/2021

Reviewed on 12/21/2021

1 Identification

- **Product identifier**
- **Trade name:** POLYFLEX 207 CATALYST
- **Article number:** WP207A.0
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**
Wasser Technologies
4118 B PL NW, Suite B
Auburn, WA 98001, US
Phone 253-850-2967
- **Information department:** Product safety department
- **Emergency telephone number:**
EMERGENCY PHONE NUMBERS:
USA and Canada: 1-800 424-9300

2 Hazard(s) identification

- **Classification of the substance or mixture**
Skin Irrit. 2 H315 Causes skin irritation.
Eye Irrit. 2A H319 Causes serious eye irritation.
Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens. 1 H317 May cause an allergic skin reaction.
Carc. 2 H351 Suspected of causing cancer.
STOT SE 3 H335 May cause respiratory irritation.
STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

- **Label elements**
- **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



- **Signal word** Danger
- **Hazard-determining components of labeling:**
4,4'-methylenediphenyl diisocyanate
o-(p-isocyanatobenzyl)phenyl isocyanate
- **Hazard statements**
H315 Causes skin irritation.
H319 Causes serious eye irritation.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H335 May cause respiratory irritation.
H373 May cause damage to organs through prolonged or repeated exposure.
- **Precautionary statements**
Keep out of reach from children.
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust/fume/gas/mist/vapors/spray.
P264 Wash thoroughly after handling.

(Contd. on page 2)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/22/2021

Reviewed on 12/21/2021

Trade name: **POLYFLEX 207 CATALYST**

(Contd. of page 1)

- P271 Use only outdoors or in a well-ventilated area.
- P272 Contaminated work clothing must not be allowed out of the workplace.
- P280 Wear protective gloves/protective clothing/eye protection/face protection.
- P284 [In case of inadequate ventilation] wear respiratory protection.
- P302+P352 If on skin: Wash with plenty of water.
- P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
- P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308+P313 IF exposed or concerned: Get medical advice/attention.
- P312 Call a poison center/doctor if you feel unwell.
- P321 Specific treatment (see on this label).
- P314 Get medical advice/attention if you feel unwell.
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
- P337+P313 If eye irritation persists: Get medical advice/attention.
- P342+P311 If experiencing respiratory symptoms: Call a poison center/doctor.
- P363 Wash contaminated clothing before reuse.
- P403+P233 Store in a well-ventilated place. Keep container tightly closed.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**· **NFPA ratings (scale 0 - 4)**· **HMIS-ratings (scale 0 - 4)**· **Other hazards**· **Results of PBT and vPvB assessment**· **PBT:** Not applicable.· **vPvB:** Not applicable.

3 Composition/information on ingredients

· **Chemical characterization: Mixtures**· **Description:** Mixture of the substances listed below with nonhazardous additions.· **Dangerous components:**

101-68-8	4,4'-methylenediphenyl diisocyanate	10-30%
5873-54-1	o-(p-isocyanatobenzyl)phenyl isocyanate	5-10%

US

(Contd. on page 3)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/22/2021

Reviewed on 12/21/2021

Trade name: **POLYFLEX 207 CATALYST**

(Contd. of page 2)

4 First-aid measures

- **Description of first aid measures**

- **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

- **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- **After swallowing:** If symptoms persist consult doctor.

- **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

- **Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

5 Fire-fighting measures

- **Extinguishing media**

· **Suitable extinguishing agents:** Use fire fighting measures that suit the environment.

- **Special hazards arising from the substance or mixture**

During heating or in case of fire poisonous gases are produced.

- **Advice for firefighters** Not available

· **Protective equipment:** Mouth respiratory protective device.

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures** Mount respiratory protective device.

- **Environmental precautions:**

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

- **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

- **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· **Information about protection against explosions and fires:** Keep respiratory protective device available.

(Contd. on page 4)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/22/2021

Reviewed on 12/21/2021

Trade name: POLYFLEX 207 CATALYST

(Contd. of page 3)

- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No information available.
- **Control parameters**
- **Components with limit values that require monitoring at the workplace:**
The following constituent is the only constituent of the product which has a PEL, TLV or other recommended exposure limit.
At this time, the remaining constituent has no known exposure limits.

101-68-8 4,4'-methylenediphenyl diisocyanate

PEL	Ceiling limit value: 0.2 mg/m ³ , 0.02 ppm
REL	Long-term value: 0.05 mg/m ³ , 0.005 ppm Ceiling limit value: 0.2* mg/m ³ , 0.02* ppm *10-min
TLV	Long-term value: 0.005 ppm

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
Use splash goggles, solvent resistant gloves. Long-sleeved clothing ideally made of cotton. A cartridge mask.
- **General protective and hygienic measures:**
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Store protective clothing separately.
Avoid contact with the eyes and skin.
- **Breathing equipment:**
The likelihood of overexposure in non-spray, non-heated applications of coatings containing polyisocyanates is reduced due to the low volatility and vapor pressure of these materials. Hence, the application of polyurethane coatings by trowel, brush, paint mitt, roller, or squeegee reduces the likelihood of inhalation overexposure to airborne diisocyanate vapors. However, appropriate measures must be established to prevent skin/eye contact during these applications. When air concentrations are not known (or above the TLV), an air-supplied respirator is required. Refer to OSHA Respiratory Protection Standard (29 CFR 1910.134). In presence of air movement, air-purifying (cartridge type) respirators are not the best protection but can be used, if you replaced them frequently. Change cartridges after 8h max or less due to their low warning properties. When in a confined space wear MSHA/NIOSH approved self-contained breathing apparatus or equivalent and full protective gear ref. SSPC-TU 8.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

(Contd. on page 5)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/22/2021

Reviewed on 12/21/2021

Trade name: **POLYFLEX 207 CATALYST**

(Contd. of page 4)

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:	Liquid
Color:	Amber colored
Odor:	Light
Odor threshold:	Not determined.

· **pH-value:** Not determined.

· **Change in condition**

Melting point/Melting range:	Undetermined.
Boiling point/Boiling range:	208 °C (406.4 °F)

· **Flash point:** 177 °C (350.6 °F)

· **Flammability (solid, gaseous):** Not applicable.

· **Decomposition temperature:** Not determined.

· **Auto igniting:** Product is not selfigniting.

· **Danger of explosion:** Product does not present an explosion hazard.

· **Explosion limits:**

Lower:	Not determined.
Upper:	Not determined.

· **Vapor pressure at 20 °C (68 °F):** 0 hPa

· **Density at 20 °C (68 °F):** 1.07 g/cm³ (8.92915 lbs/gal)

· **Relative density** Not determined.

· **Vapor density** Not determined.

· **Evaporation rate** Not determined.

· **Solubility in / Miscibility with**

Water: Fully miscible.

· **Partition coefficient (n-octanol/water):** Not determined.

(Contd. on page 6)

US

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/22/2021

Reviewed on 12/21/2021

Trade name: POLYFLEX 207 CATALYST

(Contd. of page 5)

- | | |
|----------------------------------|--|
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| · Solvent separation test | |
| VOC content: | 0.00 %
0.0 g/l / 0.00 lb/gal |
| · Other information | No further relevant information available. |

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** The product is stable at room temperature.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**

- **Acute toxicity:**

- **LD/LC50 values that are relevant for classification:**

101-68-8 4,4'-methylenediphenyl diisocyanate

Oral LD50 2,200 mg/kg (mouse)

- **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.

- **on the eye:** Irritating effect.

- **Sensitization:**

Sensitization possible through inhalation.

Sensitization possible through skin contact.

- **Additional toxicological information:**

The product shows the following dangers according to internally approved calculation methods for preparations:

Harmful

Irritant

- **Carcinogenic categories**

- **IARC (International Agency for Research on Cancer)**

101-68-8 4,4'-methylenediphenyl diisocyanate

3

- **NTP (National Toxicology Program)**

None of the ingredients is listed.

- **OSHA-Ca (Occupational Safety & Health Administration)**

None of the ingredients is listed.

US

(Contd. on page 7)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/22/2021

Reviewed on 12/21/2021

Trade name: POLYFLEX 207 CATALYST

(Contd. of page 6)

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

14 Transport information

· UN-Number	
· DOT, ADR, IMDG, IATA	Void
· UN proper shipping name	
· DOT, ADR, IMDG, IATA	Void
· Transport hazard class(es)	
· DOT, ADR, ADN, IMDG, IATA	
· Class	Void
· Packing group	
· DOT, ADR, IMDG, IATA	Void
· Environmental hazards:	Not applicable.
· Special precautions for user	Not applicable.
· Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	Void

 US
 (Contd. on page 8)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/22/2021

Reviewed on 12/21/2021

Trade name: POLYFLEX 207 CATALYST

(Contd. of page 7)

15 Regulatory information

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

No further relevant information available.

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredients is listed.

· **Section 313 (Specific toxic chemical listings):**

101-68-8 4,4'-methylenediphenyl diisocyanate

· **TSCA (Toxic Substances Control Act):**

4,4'-methylenediphenyl diisocyanate

ACTIVE

o-(p-isocyanatobenzyl)phenyl isocyanate

ACTIVE

· **Hazardous Air Pollutants**

101-68-8 4,4'-methylenediphenyl diisocyanate

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

· **Carcinogenic categories**

· **EPA (Environmental Protection Agency)**

101-68-8 4,4'-methylenediphenyl diisocyanate

D, CBD

· **TLV (Threshold Limit Value)**

None of the ingredients is listed.

· **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients is listed.

· **GHS label elements** The product is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms**



· **Signal word** Danger

· **Hazard-determining components of labeling:**

4,4'-methylenediphenyl diisocyanate

o-(p-isocyanatobenzyl)phenyl isocyanate

· **Hazard statements**

H315 Causes skin irritation.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317 May cause an allergic skin reaction.

H351 Suspected of causing cancer.

(Contd. on page 9)

Safety Data Sheet

acc. to OSHA HCS

Printing date 12/22/2021

Reviewed on 12/21/2021

Trade name: POLYFLEX 207 CATALYST

(Contd. of page 8)

*H335 May cause respiratory irritation.**H373 May cause damage to organs through prolonged or repeated exposure.***· Precautionary statements***P201 Obtain special instructions before use.**P202 Do not handle until all safety precautions have been read and understood.**P260 Do not breathe dust/fume/gas/mist/vapors/spray.**P264 Wash thoroughly after handling.**P271 Use only outdoors or in a well-ventilated area.**P272 Contaminated work clothing must not be allowed out of the workplace.**P280 Wear protective gloves/protective clothing/eye protection/face protection.**P284 [In case of inadequate ventilation] wear respiratory protection.**P302+P352 If on skin: Wash with plenty of water.**P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.**P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.**P308+P313 IF exposed or concerned: Get medical advice/attention.**P312 Call a poison center/doctor if you feel unwell.**P321 Specific treatment (see on this label).**P314 Get medical advice/attention if you feel unwell.**P362+P364 Take off contaminated clothing and wash it before reuse.**P333+P313 If skin irritation or rash occurs: Get medical advice/attention.**P337+P313 If eye irritation persists: Get medical advice/attention.**P342+P311 If experiencing respiratory symptoms: Call a poison center/doctor.**P363 Wash contaminated clothing before reuse.**P403+P233 Store in a well-ventilated place. Keep container tightly closed.**P405 Store locked up.**P501 Dispose of contents/container in accordance with local/regional/national/international regulations.***· Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Department issuing SDS: Product safety department**· Contact:** HS REG.DEPART.REG.SS**· Date of preparation / last revision** 12/22/2021 / -**· Abbreviations and acronyms:***ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)**IMDG: International Maritime Code for Dangerous Goods**DOT: US Department of Transportation**IATA: International Air Transport Association**EINECS: European Inventory of Existing Commercial Chemical Substances**ELINCS: European List of Notified Chemical Substances**CAS: Chemical Abstracts Service (division of the American Chemical Society)**NFPA: National Fire Protection Association (USA)**HMIS: Hazardous Materials Identification System (USA)**VOC: Volatile Organic Compounds (USA, EU)**LC50: Lethal concentration, 50 percent**LD50: Lethal dose, 50 percent**PBT: Persistent, Bioaccumulative and Toxic**vPvB: very Persistent and very Bioaccumulative**NIOSH: National Institute for Occupational Safety**OSHA: Occupational Safety & Health**TLV: Threshold Limit Value**PEL: Permissible Exposure Limit*

(Contd. on page 10)

Safety Data Sheet
acc. to OSHA HCS

Printing date 12/22/2021

Reviewed on 12/21/2021

Trade name: POLYFLEX 207 CATALYST

(Contd. of page 9)

*REL: Recommended Exposure Limit**Skin Irrit. 2: Skin corrosion/irritation – Category 2**Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A**Resp. Sens. 1: Respiratory sensitisation – Category 1**Skin Sens. 1: Skin sensitisation – Category 1**Carc. 2: Carcinogenicity – Category 2**STOT SE 3: Specific target organ toxicity (single exposure) – Category 3**STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2*

US